

...from a small blacksmith shop...

to one of the nation's leading manufacturers of quality hand tools . . .

Hold any P & C tool in your hand. Notice the quality. Try using it. Notice how it "feels good" in your hand. It's perfectly balanced. P & C Tools are truly quality tools. And it all started many years ago in a small blacksmith shop way out west.

Many people have asked what the initials "P & C" mean. Actually, they are the initials of the two master mechanics who started our company in 1920, John Peterson and Charles Carlborg. These two skilled blacksmiths began making hand tools for their own use. They made these tools from Model T Ford axles and crankshaft steel. They were excellent tools. Soon other mechanics and craftsmen asked to buy them. And so Peterson and Carlborg were in the tool business. Today, you'll find P & C Tools sold in quality stores all over America, in every state in the Union and in many foreign countries.

Peterson and Carlborg never compromised with quality.

P & C Tools had to be good. Through the years the philosophy of quality has remained as the never ending goal at P & C.



NOTICE: Due to Government restrictions or other causes, all P & C tools, prices, finish, design, steel analyses and other specifications are subject to change without notice.

Box 5926, Portland 22, Oregon

Phone Olive 4-5471 Cable Address: PANDCTOOL



P&C Tools are America's finest quality tools. They are made from the very best steels and alloys obtainable. Every P&C Tool is made by a skilled P&C master craftsman and each tool is carefully inspected before leaving our factories. P&C tool are made according to the very highest standards so they will hold up for years and years of hard wear. All P&C Tools will hold up for years and years of hard wear. All P&C Tools are guaranteed free from defects in material and workmanship. If any P&C tool ever proves defective . . . in any way . . . from causes other than normal wear or abuse . . . P&C has authorized its dealer to replace or repair that tool at no charge to the buyer.

SUBSIDIARY OF

See latest price list for prices

The **BEST TOOLS** money can buy

Copyright 1959, P&C Tool Company

GENERAL INDEX

Page	Page	Page	Page
Tool No.	Tool No-	Tool No.	Tool No.
Adaptors	Duck Bill Pliers 5 Drills, Star	Offset Calkers	Combination Pattern. 5
14" Drive Sockets 8		Open and wanted care of	Sockets and Socket Sets. 8-12
Drive Sockets 8. 9	Electricians' Screwdrivers 1	Parrot Nose Wrench	%" Drive 8
Step Plate13	Expander, Tubing13 Extensions	Pliers 4 Parts Kits	16" Drive
Adjustable Wrenches 6	Socket 7, 8, 9, 10, 11 Extractor Set, Screw	Adjustable Wrenches. 6	" Drive11, 12
Aligning Punch 3 Awl, Tire Prodding18	Extractor Set, Screw and Pipe	Dina Wranches 5	1" Drive
Awt, the Flouding	man + the + () + + + + + + + + + + + + + + + + +	%", ½", ¾" Drive Ratchet 7, 8, 9, 10	Extensions7. 9, 10, 11
Bars, Lining Up15	Feeler Gauges	Pecking Hammer	Metric
Battery Pliers	Holder	Long	Universal7, 8, 9, 10
Bearing Separator and	Set	Short	Soil Pipe Chisels12
Puller Attachment 14	Bent	Pin Punches 3	Spark Plug Gauge Set17 Special Purpose Tools.15, 20
Bending Irons	File Double Faced	Pipe Wrenches 5	Grab All
Combination Pliers 3	Flexible Straight	Heavy Duty 6 Internal 12	Special Tools
Made	File and Holder	Parts Kli	Speeder Handles8, 9, 10 Spinner Handle8
Long Feeler Gauge16 Short Feeler Gauge16	Floor Chisels	Stillson 5 Piston Ring Compressor. 16	Star Drills
Body and Fender Tools17	Ford V-8 Connecting	Pliers3-4-5	Starter Punches 3 Steering Wheel Puller 14
Box Wrenches 7	Ford V-8 Connecting Rod Socket	Handeze Grips 3	Step Plate Adaptors15
Box. Ratcheting Wrench. 8 Box Wrench Set		Lever Wrench	Step Plate Adaptors15 Stillson Pipe Wrenches 5 Structural Wrenches18
How and Open End	Gads, Concrete	Pliers, Midget 5	Structurat Wrenches18
Wrenches	Gasket Scraper	Parallel Jaw Lock Ring	Telephone Pliers 4
Brake Gauge Set17	Gauges, Feeler16	Self Energizing Gear	Telephone Pliers 4 T-Handle, Sliding, 7, 8, 9, 10
Brake Spring Pliers 5	Gauge Set Brake	Self Energizing Gear Lock 4 Special Plumber's 4	Thin Head, Open End 5 Thin Jaw Combination
Brass Hammer17	Ignition16	Plumbing Tools12	Pliers 3
Cadillas and LaSalla Can	Short Blade	Prick Punches 3	Tire Iron
Cadillac and LaSalle Con- necting Rod Socket15	Step-Cut	Pullers Tomatani 12	Cabinets
Calkers	Grab All	Bearing Separator	Cabinets
Broad Curved Nose . 13	Grips, Handeze plier 2	Attachment14 Collet Type Blind	Tubing Expander 13
Curved Pony13	Hammers 17-18	Collet Type Blind	
Gasket 13 Left and Right 13 Long 13	Brass	Bearing15 Heavy Duty13	Universal Joint. 7, 8, 9, 10, 12
Long 13	Finishing18	Medium Dury 13	Universal Pilers,
Utiset	Long Body17	Slide Hammer 14 Steering Wheel 14 Three-Jaw Light	Heavy Duty 3 Utility Pliers.
Water Main13	Finishing 18 Long Body 17 Long Pecking 17 Magnetic Trim 17	Three-Jaw Light	Multiple Groove 4
Carburetor Jet Wrench. 16	Handles	Duty 14 Two-Jaw Light Duty 14 Universal Wheel 14 Wedge Type Stud 15 Inside Jaw 15 Single Jaw 15 Lone Cuttide Jaw 15	Valve Lifter
Celling Calkers	Hammer	Universal Wheel 14	
Center Punches 3 Chest, Master Tool 19 Chisels 2-3	Sliding T10	Wedge Type Stud15	Water Main Calker13
Chisels2-3	Speeder	Single Jaw15	Water Pump Pilers Heavy Duty 4
Floor	Heavy Duty Diagonal	DOME O'LLEGE OF 11 LAP	Heavy Duty 4 Medium Duty 4
Clik-Stop Adjustable	Spinner	Punches	Wheel Puller
Wrench 5	Heavy Duty Universal	Ratchet,	Screwdrivers 1
Clutch Head Screwdrivers 2	Pliers	Reversible7, 8, 9, 10, 11 Ratchetor, 1, Drive10	Wrenches
Cold Chisels 2 Combination Pliers	Holder	Rivet Shear 2	Adjustable 6 Adjustable, Parts Kit. 6
Bent Nose Thin Jaw 3	Feeler Gauge17 File18	Rivet Shear	Adjustable, Parts Kit. 6 Box
Side Cutting Slip Joint 3		Screw and Pipe Extractor	Carburetor Jet16
Combination Wrenches 6	Ignition Gauge Set16 Ignition Pliers, Slip Joint. 2	Set	Combination 6
Combination Wrench Set. 6 Compressor, Piston Ring 16	Internal Pipe Wrench13 Irons, Bending13	Screwdrivers	Lug18
Concrete Gads	Irons, Hending13	Double End Offset 2 Electricians' 1	Metric
Connecting Rod Sockets 14	L-Handie11	Electricians' 1 Mechanics' 2	Obstruction
Cutting and Special Pliers 4	L-Handle	Phillips	Open End
Deep Sockets 7	Pliers	Societ 9-0	Thin Head 5
Diagonal Cutting Pliers,	Lining Up Bars	Wood Handle 2 Service Station Tools	Wrench Pliers
Diamond Point Chisels 3	Long Nose Wrench Pliers. 4 Lug Wrench, Four Way18	Shear, Rivet Chisel 2	Long Nose 4
Dinging Hammer17		Side Cutting Pliers Needle Nose 4	Parrot Nose 4
Egg Shaped18	Magnetic Trim Hammer 17	Slip Joint	Wrench Sets Box 7
New Bead18	Mechanics' Screwdrivers, 1 Metric Wrenches20	Combination 3	Combination 6
Radius	Midget Wrenches, Set 7	Slide Hammer Puller14 Sliding	Midget 7 Open End 7
Semi-Elliptical Heel .18	Multiple Groove Utility Pliers 4	T-Handles, 8, 9, 10, 11, 12	Open mad
Shrinking18		Slip Joint Pliers 3	Yarning Irons
Double End Offset Screwdrivers 2	Needle Nose Side Cutting Pliers 4	Snips Multiple-leverage 5	Offset
Drag Link Adjuster10	Containg Pacts	Duckbill 5	Yarning Irons and
Drift Punches 3	Obstruction Wrenches 16	Straight 5	Calkers13
CATALOG NUMBER	P INDEY		
CATALOG NUMBE	KINDEX		
Tool Page	Tool Page	Tool Page	Tool Page
000-AA-020/216	Tool No. 132L-132R	1257-12913. 4	529519
0200-A-0280	133-135	13031 - 1332 5	5495-5695

Tool	Page No.	Tool	Page No.
000-AA-020/2	16	132L-132R	
0200-A-0280	В	133-135	
03315-03456	13	13515-135%	
5-7/16-69gx18	12. 13	136	7 X
9A-19	2	13612	
1314-1434×15	12, 13	137	7 1
20-21	3	140	13 2
2135	12	140-D	
22-33	3	141-142	
3315-3396	13	164-166	
34	3	207	
3716-3794	12	230	18 2
40-76	3	302-303	15 3
8434-84-1	SILLIN	402-878	2 3
88-92	2, 3	914-1176	18 3
101-103	15	1191-1196	8 4
107%-119		1200S-1209	3. 4 4
130%-131%	40	1215-1234	4.5 4
191 199	13	1235-1248	3, 4 4
131-132		1251	5 4

	Page		Page
Tool	No.	Tool	No.
257-1291	3. 4	5295	19
303L-1332	5	5495-5695	15
419-1509	17, 18	5894	11. 19
1704-X1720-S	6	6000 CR-6000NR	
725-1731	16	6012	
806-1824HD	6	6014-6018	
018-2130	15	6016H-6024H	
234-2264	7	6019	
316-2343	16	6020	
401-2536	7	6021	13
700-B-2918	7	6022-6024	11
710M-2722M	20	6025-6040	
008M-3019M	20	6071-6265	10, 11
000-F-3324	9	6305-6539	15, 16
114H-3118H	20	9071-9368	11, 12
000-D-4068	14	9500-A	
067	15	9500-oc-9509	12
070-C-4080	14, 15	9521-9529	17
515-4532	15	9552-9612	12
795		9970-9990	19

Quick Index **Finder**



This handy thumb index will guide you quickly to inside pages. Do as the hand Illustrates at right matching section on master index with solidcolor block on serresponding page inside.

> SCREWDRIVERS CHISELS, PUNCHES Page 2

> > PLIERS AND WRENCHES Pages 3-7

PLIERS, SNIPS, & PIPE WRENCHES Pages 5-6

> SOCKETS AND ATTACHMENTS Pages 7-12

PLUMBING TOOLS WHEEL PULLERS Pages 12-15

SPECIAL PURPOSE TOOLS Page 15

FEELER GAUGES BODY & FENDER TOOLS Pages 16-17

HAMMERS SERVICE STATION TOOLS Pages 17-18

TOOL CHESTS BOXES, CABINETS Page 19

> METRIC WRENCHES Page 20

P&C...the best tools money can buy...



SCREWDRIVERS

Handles are shock proof, fire resistant, uniformly clear plastic. Hammer proof, acid proof, they will not absorb grease. Rounded top, deeply fluted, tapered near bottom with knurled tip. Extra long shanks, blades forged from special analysis alloy steel, heat treated, oil tempered. Bits highly polished to resist rust, torque tested against twisting. Tough, hardened, precision ground tip will not chip, stays sharp.

PLASTIC HANDLE



ROUND SHANK, Keystone type

No.	Diam.	Blade	Length	Wt. Lbs
402	1/8"	21/2"	53/4"	.05
404	1/8"	41/2"	71/4"	.06
504	3/16"	4"	71/2"	.10
508	3/16~	71/6~	11"	.13
634	1/4"	4"	8"	.17
736	5/16"	8"	10%"	.30
740	5/16"	10"	14%"	.39
838	3/8"	8"	13"	.47

ROUND SHANK Cabinet type

Bloo	Cina	Plade I	man and he	1274	T lun
140'	Size	Blade I	SCHEUT.	77 -	LIN
	@ 48.0m				
505	3/16~	S.V	8%"		.13



SQUARE SHANK, Keystone Type

No.	Size	Blade L	ength V	Vt. Lbs
442	1/8"	21/2"	51/4"	.04
501	3/16"	1¼"	30	.07
544	3/16"	4"	736.0	.11
548	3/16"	71/2"	10%"	.15
601	1/4"	714" 114" 4" 9" 8"	37/4" 8"	.13 .15 .25 .33
604	1/4"	4"	8"	.15
609	1/4"	9"	13"	.25
706	5/16"	6"	1034**	.33
710	5/16"	10- 8" 12- 16"	14½" 13" 19" 23"	.55
808	3/8"	8"	13"	.55
812	3/8"	12"	19"	.90
816	3/8"	16"	23"	1.05



WOOD HANDLE (OCTAGON)



Made of seasoned, selected, clear Birch with natural finish. Rounded metal cap protects top of handle. Steel rivet through cap, handle and blade holds them as one. Same tough, steel shank and tempered blade. Steel ferrule protects blade end of handle. Seven sizes for slotted screws.

	DAGATOR DE			
No.	Diam.	Blade	Length	Wt. Lbs.
551	3/16" a		41/6"	.10
553	3/16"	21/2"	6%"	.12
559	3/16"	-	131/4"	.17
654	1/4"	4"	91/6"	22
660	1/4"	914"	141/2"	.30
756	5/16"	6"	12"	.42
760	5/16"	10"	16"	.50

ALL PURPOSE SCREWDRIVER SET




No.	Shank	Blade	Length
A82	Diam. 1/8"	21/2"	544"
504	Diam. 3/16"	4"	71/2"
674	Phillips No. 2	4"	8"
706	5/16" square	6"	101/2"

Set No. 4—All-Purpose Screwdriver Set—Wt, 1,0 lbs.

WOOD HANDLE PHILLIPS

For Phillips head screws, without metal cap on handle.

No.	Blade Size	Blade	Length	Wt. Lbs.
523	1	3"	61/4"	.08
624	2	4"	872"	.18
726	3	6"	12"	.30
828	4	811	141/2"	.52



Precision machined, heat treated bits give exact fit in Phillips cross-slot screws. Five screwdriver sizes will fit 25 Phillips head screw sizes. Chrome plated shank.

No.	Phillips Blade Size	Blade	Length	Wt. Lbs
573 670 674 776 878	1 2 2 3 4	3" 4" 6" 814"	6½" 2½" 8" 10½"	.10 .08 .15 .28

DOUBLE END OFFSET



Blades at right angles to each other on opposite sides of handle. Heat treated bits highly polished, over-all rust resistant. Works fine in close quarters.

d'um re	40.		
No.	Stock	Length	Wt. Lbs.
164	1/4"	43/4"	.07
165	5/16"	5"	.11
166	3/8"	614"	.19

PLASTIC HANDLE CLUTCH HEAD




Type G design bits are precisely machined for accurate fit on screws with "Figure 8" or "Butterfly" type heads. Round, chrome plated, torque tested shanks.

Tool No.	Bit Size	Blade Length	Overall Length	Weight Lbs.
483	5/32"	31/4"	7%"	.12
584	3/16"	37/6"	7%"	.12
685	1/4"	4%"	8%"	.18
786	5/16"	47/8"	9%"	.28

CHISELS

Beveled heads, sandblasted, grey satin finish, large octagon handles, highly polished taper or bevel, precision ground point or cutting edge. Hot forged from special analysis alloy steel scientifically tempered to cut any metal that can be filed. Big octagon handles easy to hold, easier to hit, will not chip. Every tool lacquer-dipped to resist rust.

3 piece PUNCH and CHISEL set



Includes: Cold Chisel No. 12 Center Punch No. 22 Starter Punch No. 66 Plastic Kit

Set No. 9 Wt. .45 lbs.

COLD CHISELS

All Property of the Parket	The M	NO.	= (F-C)	
No.	Stock Size	Cut	Length	Wt. Lbs.
9-A	3/16"	1/4"	41/8"	.03
10	1/4"	9/32"	51/6"	.08
11	5/16"	3/8"	5%"	.13
12	3/8"	7/16"	51/2"	.18
12-A	7/16"	1/2"	6"	.24
13	1/2"	9/16"	6%"	,33
14	19/32"	11/16"	7"	.53
15	23/32"	13/16"	8"	.78
17	23/32"	13/16"	12"	1.43
17-A	13/16"	1"	83/10	1.26
18	13/16"	1"	12**	1.93
19	15/16"	13/16"	12"	2.4

RIVET SHEAR CHISELS



CAPE CHISELS

Stock Cut Length Wt. Lbs. No. Size Size 1/4" 3/16" 41/2" .08 31 5/16" 1/4" 51/4" .13 3/8" 5/16" 534" .18 32 33 1/2" 3/8" 61/4" .33

ROUND NOSE CHISELS

,50

7/16"

5/8"



DIAMOND POINT CHISELS

-	THE BUSINESS		PAC.	
	Stock	Cut		
No.	Size	Size	Length	Wt. Lbs.
40	1/4"	5/32"	41/6"	.08
41	5/16"	3/16"	5 ^N	.13
42	3/8"	7/32"	51/2"	.18
43	1/2"	9/32"	6"	.33

PED PUNCHES

CENTER PUNCHES

NT. C1 2 C1 T	Wt Lbs
No. Stock Size Length	
20 1/4" 4"	.05
21 5/16" 43/2"	.10
22 3/8" 43/4"	.15
22A 7/16" 4%"	.19
23 1/2" 5"	.25
24 5/8" 6"	.45

PRICK PUNCHES

		4.6		
No.	Stock Size	Length	Wt. Lbs.	
27	1/4"	43/6"	.08	
28	5/16"	5"	.10	
29	3/8"	51/2"	.15	


DRIFT PUNCHES

No.	Stock Size	Point Diam.	Length	Wt. Lbs.
70	1/4"	3/32"	10"	.10
71	5/16"	1/8"	10"	.15
72	3/8"	3/16*	10"	.23
73	7/16"	7/32=	10"	.33
74	1/2"	1/4"	10"	.43
75	5/8"	5/16"	10"	.68
76	3/4"	3/8"	10"	1.00

ALIGNING PUNCH

No.	Stock	Point	Length	Wt. Lbs.
88	5/8"		16"	.98

STARTER PUNCHES




PIN PUNCHES

	Stock	Point	Point		Wt.
No.	Size	Diam.	Length	Length	Lhs.
58	1/4"	1/16"	11/4"	43/4"	.05
60	1/4"	3/32"	11/4"	41/4"	.05
61	5/16"	1/8"	1%"	41/2"	.08
62	5/16"	5/32"	1%"	5"	.10
63	3/8"	3/16"	1%"	51/4"	.13
64	7/16"	7/32"	2%"	514*	.18
64-1	1/2"	1/4"	2%"	53/4"	.23

PER SPECIAL TOOL SETS

24 piece PUNCH and CHISEL set



One each of the following:
Cold Chisels Nos. 10, 11, 12, 13, 14
Cape Chisels Nos. 30, 31, 32, 33
Diamond Chisels Nos. 40, 41, 42
Round Nose Chisels Nos. 50, 52
Center Punches Nos. 21, 23
Prick Punch No. 27
Pin Punches Nos. 60, 61, 62, 63, 64
Starter Punches Nos. 66, 67 in Tool Kit
No. 2401, 8"x25½", 23 pockets.
Set No. 1. Wt. 3.8 lbs.

HANDEZE PLIER GRIPS



Resilient P&C blue plastic tubes slip over plier handles easily to give better, more comfortable grip. Stay on permanently, fit tight.

Long wearing . . , they're rugged. Finest quality plastic. Unaffected by oil and grease. Resist tear and damage. Backed by famous P&C guarantee. 3 sizes fit practically all pliers.

12005 —Small size 1200M—Medium size 12001 —Large size

PEG R PLIERS

Scientifically designed, forged from highest quality alloy steel. Deeply milled teeth oil tempered to retain sharpness, insure positive grip. Tempered joint-bolts hold job-shaped jaws in perfect alignment. All have polished heads and slip-joint pliers are chrome plated against rust. Cutting edges are induction hardened against chipping and dulling. Scientifically engineered leverage and balance.

Page 3

PER SLIP JOINT PLIERS

COMBINATION



Shear type cutter in throat. Aligned holes near joint for precise ahear cutting take wire up to \%".

No.	1275	Length 5"	Wt26	Ibs.
	1276	6"	.41	
	1278	8"	.50	
	1280	10"	.88	

SIDE CUTTING SLIP JOINT COMBINATION



All the features of slip joint combination pliers plus durable, induction hardened side cutter and extra strong tempered bolt.

No. 1246 Length 6" Wt. .49 lbs.

THIN JAW COMBINATION



No. 1201 Length 5" Wt. .25 lbs. 1202 6" .35

BENT NOSE THIN JAW COMBINATION



Thin jaws offset 30° make handy nail or staple puller.

No. 1203 Length 7" Wt. 43 lbs.

HEAVY DUTY UNIVERSAL



One jaw curved to grip round or irregular objects, other jaw straight with groove for gripping wire, pins or nails.

No. 1257 Length 7" Wt. .58 lbs.

MIDGET SLIP JOINT



Three slip joint positions allow parallel opening up to "".

No. 1235 Length 41/2" Wt. .07 lbs.

P&C...the best tools money can buy...

PARROT NOSE WRENCH



Pipe wrench design gives firm grip. Powerful leverage from four slip joint positions gives wide capacity. Nose offset 75° to reach awkward jobs.

No. 1236 Length 6" Wt. .41 lbs. 1238 71/2" .61

LONG NOSE WRENCH



Milled teeth and powerful leverage, long, slender nose, offset 20°, holds objects in front of center, gives extra grip.

No. 1239 Length 8" Wt. .54 lbs.

LEVERAGE PLIER



"A chest of tools in one," this revolutionary plier is perfect for countless jobs, and is a "must" of all tool users. Patented, three-piece compound leverage design multiplies applied pressure ten times! Non-slip jaws open 1½ inches.

No. 1234 Length 8" Wt. .62 lb.

SPECIAL PLIERS

NEEDLE NOSE SIDE CUTTING



Long, thin taper, firm grip and spring tempered jaws. Flush joint is precision fitted for wobble-free action, keeps keen edges of hand honed side cutters aligned perfectly.

No. 1226 Length 6" Wt. .28 lbs.


LONG THIN NEEDLE NOSE PLIER



Has very thin nose for getting into places with restricted clearance.

No. 1222 Length 61/2" Wt. .22 lb.

MEDIUM DUTY WATER PUMP



Has same versatile features and adjustments of No. 1240, but is only 942'' thick.

No. 1241 Length 91/2" Wt. .58 lbs.

LEVER WRENCH PLIER



Five tools in one . . . a powerful hand vise, a clamp, an adjustable wrench, a pipe wrench, and a plier. To operate, place the object to be held between the jaws and turn the screw at the end of one handle until the jaws grip the work snugly. Then, squeeze the handles together. This forces the central fulcrum beyond the "in line" position and locks the jaws in the holding position with pressure up to one ton. Capacity 1½ inch.

No. 1291 Length 8" Wt. 1 lb.

MULTIPLE-GROOVE UTILITY



Five tongue-and-groove adjustments, plus slip joint, provide wide range of openings. Grooves hold jaws securely in desired position, taking strain off

No. 1242 Length 11/2" Wt. .44 lbs. No. 1243 Length 91/2" Wt. .81 lbs.

CURVED THIN NEEDLE NOSE PLIER



Same as No. 1222 plier, except nose is bent at 79° angle. Handy for reaching around objects.

No. 1225 Length 6" Wt. .22 lb.

HEAVY DUTY DIAGONAL CUTTING



Tremendous leverage from short, powerful jaws set very close to solidly riveted joint. Perfect alignment, leverage, and balance for difficult cutting jobs.

No. 1209 Length 7" Wt. .49 lbs.

SELF-ENERGIZING GEAR-LOCK



In this revolutionary "Plier of Tomorrow," bolt slides into slanting gear-type slots. As handles are squeezed, bolt locks in chosen slot and jaw pressure increases. Design eliminates slipping, prevents binding and wear of bolt and slot, and permits smooth, visible adjustments in five slots. Other features include slim jaws, 134" opening, sharp pipe wrench teeth, and powerful, novel, no-bend cutter.

No. 1245 Length 944" Wt. .66 lbs.

HEAVY DUTY WATER PUMP



No. 1240 Length 91/2" WL .58 lbs.

SPECIAL PLUMBER'S PLIER



For use on plated plumbing fixtures. Opens to 21/2". Microgroove adjustment permits parallel alignment of jaws.

No. Length Wt.

1248 with Brass and Nylon Insert Jaws 113/a" .9 lb.

12485 with Smooth Steel

Jaws 11%; " .9 lb.

Jaws 113/18" .9 lb.

DIAGONAL CUTTING



Cutting edges are induction hardened and hand honed after assembly for lasting sharpness.

No. 1204 Length 41/2" Wt. .20 lbs.

1206 6" .37 1207 7" .54

TELEPHONE



Excellent for manipulating wire and wiring. Heavy, flush riveted joint and shear-type wire cutter.

No. 1260 Length 6" Wt. .25 lbs.

LINEMAN'S SIDE CUTTING



Hand honed edges of induction hardened cutters are kept perfectly aligned by extremely heavy and tempered flush steel joint bolt.

No. 1266 Length 6" Wt. 43 lbs. 1268 8" 81

GAS



Deep, sharp teeth are milled in two sizes on the sturdy jaws to hold a wide range of tubing sizes without adjustment. Lengthwise teeth at end of jaws give positive grip on wire and pins. Heavy, flush rivet joint insures perfect alignment.

No. 1258 Length 6" Wt. .25 lbs.

BRAKE SPRING



Curved jaw clears brake shoe for close adjustment with center line of spring. Thin hooked jaw slips easily under spring. Tempered rivet and long handles give powerful leverage, extra strength.

No. 1215 Length 12" Wt. .71 lbs.

LONG REACH NEEDLE NOSE PLIERS



Extra length is useful for repair and assembly of instruments.

No. 1228 Length 8" Wt. 36 lb.

DUCK BILL



Tapered jaws 1½" and long handles give powerful leverage. Deeply milled oil tempered teeth give extra grip. Solid riveted joint.

No. 1227 Length 8" Wt. .44 lbs.

PARALLEL JAW LOCK RING



Spreads and holds lock or map pins during removal. Unique compound leverage system keeps jaws parallel.

No. 1251 Length 81/4" Wt. .54 lb.


ANGLE NOSE BATTERY



Terminal nuts manipulate easily with these thin, 30° offset jaws and long, hand fitting handles. Jaws are shaped for maximum grip regardless of nut condition. Riveted joint for extra strength. Jaw openings 5/10" to 11/6".

No. 1218 Length 8" Wt. 49 lbs.

P&C MIDGET PLIERS




No.		Length	W	Ł
	Midget Straight Nose Plier	434"	.09	lь.
1282	Midget Chain Nose Plier	434**	.10	64
1283	Midget Round Nose	-/-		

1282

1283

Plier 4½" 19 "




No.		Length	Wt.
1284 Midg	et End Cutting		
Nig	рег	4"	.10 lb.
1285 Midg	et Diagonal Ci	utting	
Pli		4"	.08 "
1286 Mide	et Flat Nose		
Plie	er	43/4"	.09 "

PEO SNIPS

Designed to give fast, smooth cuts in all types of material. Blades hot drop forged of special analysis steel and electrically heat treated and tempered. Blades designed to give uniform sheering.


DUCKBILL OR CIRCULAR



**	Overall	Length of	Wt.
No.	Length	Cut	lbs.
1307	7"	1%"	.38
1310	10"	21/4"	.84
1312	12"	3"	1.46

Page 5

STRAIGHT OR REGULAR



	Overall	Length of	WŁ
No.	Length	Cut	lbs.
317	7"	13/4"	.38
320	10"	214"	.86
322	12"	3"	1.50


MULTIPLE-LEVERAGE

Left-Right-and Straight Cut



	Overall	Length of	Wt.
No.	Length	Cut	lbs.
1303 L.	101/2"	17/10"	.70
1303 R.	101/4"	17/10"	.70
1303 5.	101/2"	1%"	.72

COMBINATION PATTERN



	Overall	Length of	Wt.
No.	Length	Cut	lbs.
1330	10"	21/4"	.88
1322	12"	3-	1.46

PEG PIPE WRENCHES

STILLSON PATTERN



Expertly made, they substantially exceed rigid Government specifications. Forged from finest, special analysis alloy steel. Deeply milled teeth oil tempered, will stay sharp for years. Rugged, hot-forged handle designed for powerful leverage. Tough, tempered rivet withstands stress. Highest quality spring steel keeps movable jaw in engaging position. Precisely milled, burr-free threads on movable jaw, easy turning, close meshed knurl, allows quick, sure adjustments. Faces, sides of jaws, frame highly polished.

No.	Max. Opening	Length	Wt. Lbs.
1806	1/2"	6"	.31
1806	3/4"	8"	.64
1810	1"	10"	1.36
1814	11/2"	14**	2.80
1818	2"	18"	4.00
1824	21/2"	24"	7.20

STILLSON PATTERN PIPE WRENCH PARTS KIT



Contains movable jaw and knurl for a single wrench. Available for all six sizes.

		Pipe	
No.	V	rench	Wt. Lbs.
X1806	for	1806	.1
X180		1808	.3
X1810	0	1810	.5
X1814	4	1814	1.0
X1818	8	1818	1.5
X182		1824	2.5
Individ	ual p	arts also	available.

See price list

PIPE WRENCHES



Features include special alloy steel; heat-treated, precision ground teeth; tapered, "I-beam" type handle; pipe sizes on movable jaw; simple design, only 4 parts, light weight and perfect believes.

No. 1806 HD	Length 6"	Wt4 lbs.
1808 HD	8"	.7
1810 HD	10"	1.5
1814 HD	14"	3.0
1818 HD	18"	5.0
1824 HD	24"	8.3

KITS FOR TOOL SETS

TOOL KIT No. 5



Includes: 6" Adjustable Wrench No. 1706

6" Slip-joint Combination Pliers No. 1276

Plastic Handle Screw-driver with 4" Blade No. 504 Plastic Kit

Kit No. 5, in 84"x44"x142"
Plastic box Wt. 1 lb.

PEG ADJUSTABLE WRENCHES



Oil tempered at points of stress, jaws are thin, light, 22½° offset. Movable jaw is hand fitted. Four heat treated threads on screw deeply knurled, accurately mesh with movable jaw. Available in 7 sizes with satin chrome finish and highly polished, rust resisting heads and handles; 7 sizes in semi-finished handles and highly polished heads. Forged from special analysis alloy steel.

FULL CHROME PLATED

]	Maximum	
No.	Length	Opening	Wt. Lbs.
1704	4"	1/2"	.08
1706	6"	3/4"	.25
1708	8"	15/16**	.53
1710	10"	1%"	.85
1712	12"	15,10"	1.61
1716	16"	17/8"	3.60
1720	20"	21/2"	6.00

SEMI-FINISH

	Maximum			
No.	Length	Opening	Wt. Lbs.	
1704-5	4"	1/2"	.08	
1706-5	6"	3/4"	.25	
1708-5	8"	15/16"	.53	
1710-5	10~	11/8"	.85	
1712-5	12"	15/16"	1.61	
1716-5	16"	1%"	3.60	
1720-5	20"	21/2"	6.00	

NEW CLIK-STOP ADJUSTABLE WRENCH


New P&C Clik-Stop wrench handles like ordinary adjustable. Merely turning Golden Knurl clicks jaw automatically into any opening wanted. It won't work lose. No buttons, levers or gadgets. Highly polished, chrome plated.

Maximum				
No.	Length	Opening	Wt. Lbs.	
1704-L	4"	1/2"	.08	
1706-L	6"	3/4"	.25	
1708-L	9"	15/16**	.53	
1710-L	10"	1%" 154.0"	.85 1 61	

SEMI-FINISH

1704-51	4"	1/2"	.08
1706-SL	6/4	3/4"	,25
1708-5L	8"	15/16"	.53
1710-SL	10"	11/6"	-85
1712-SL	12"	154a**	1.61
1716-5L	16"	17/8"	3.60
1720 EL	202	214/4	6.00

REPLACEMENT PARTS KIT



Contains movable jaw, knurl, pin and spring for a single wrench. Available for all sizes in both finishes.

No.	For Adj. Wrench	Wt. Lbs.
X1704	1704 or 1704-L	.03
X1704-5	1704-5 or SL	.03
X1706	1706 or 1706-L	.06
X1706-S	1706-5 or SL	.06

X1708	1708 or 1708-L .1
X1708-S	1706-5 or SL .1
X1710	1710 or 1710-L .2
X1710-5	1710-S or SL .2
X1712	1712 or 1712-L .3
X1712-5	1712-5 or SL .3
X1716-5	1716-5 or 51. 8
X1720-5	1720-S or St 1.3
See parte	parts also available.

COMBINATION WRENCHES



Box end offset 15° for knuckle clearance, 12 point design turns hex nut with only 15° swing. Open end at 15° angle to shank needs only 30° swing. Long handles give extra leverage, have rounded edges. Drop forged from special analysis alloy steel, oil tempered. Polished heads, satin finish handles protected by heavy chrome plate. Each wrench has same size on both ends.

No.	Opening	Length	Wt. Lbs
2708	1/4" (6 point	3"	.02
2710	5/16" (12 poin	1) 3%"	.05
2712	3/8"	41/4"	.07
2714	7/16"	51/4"	.10
2716	1/2"	61/4"	.14
2718	9/16**	77	,20
2720	5/8"	7%"	.26
2722	11/16"	8%"	.32
2724	3/4"	916"	.41
2726	13/16"	103/8"	.50
2728	7/8"	111/4"	.59
2730	15/16"	1214"	.62
2732	1"	13%"	.86
2734	11/10"	141/2"	1.03
2736	11/8"	151/2"	1.23
2740	11/4"	17"	1.70
2742	1540"	18"	1.95
2744	13/8"	19%"	2,2
2746	17/16"	20%"	2.5
2748	11/2"	21%"	2.9
2752	1%"	23"	3.2

6 piece COMBINATION WRENCH SET



Includes Nos. 2714, 2716, 2718, 2720, 2722

No. 2700-B Combination Wrench Set in No. 2427 Kit Wt. 1.7 lbs.

15 piece COMBINATION WRENCH SET

No. 2700-F Combination Wrench Set. Nos. 2710 to 2740 inclusive in No. 2413 Kit. Wt. 10 lbs.

PAB OPEN END WRENCHES



Drop forged from special analysis alloy steel with thin, tapered jaws, thin, round-edged handles. Jaw openings precisely milled for positive fit without slipping. The 15° jaw angle, by "flopping" wrench, allows continuous turning of hex nut in 30° swing.

No.	Openings	Length	Wt. Lbs.
2808	3/16" and 1/4"	41/5"	.02
2810	1/4" and 5/16"	31/2"	.05
2812	5/16" and 3/8"	4"	.06
2814	3/8" and 7/16"	41/2"	.08
2816	7/16" and 1/2"	5"	.11
2818	1/2" and 9/16"	51/2"	.15
2819	1/2" and 19/32"	63/8"	.15
2820	9/16" and 5/8"	61/2"	.21
2821	19/32" and 11/1	6" 7"	,26
2822	5/8" and 11/16	71/2"	.28
2824	5/8" and 3/4"	81/4"	.30
2825	11/16" and 3/4"	gu	.33
2828	3/4" and 7/8"	91/2"	.46
2829	13/16" and 7/8"	10"	.59
2830	7/8" and 15/16"	101/2"	.65
2831	7/8" and 11/10"	11%"	.70
2832	15/16" and 1"	111/4"	.85
2834	15/16" and 11/16	" 13"	.86
2835	I" and 1\%"	131/2"	1.10
2836	11/10" and 11/6"	13%"	1.30
2840	13 and 11/4"	14%"	1.50
2842	11/4" and 13/10"	161/4"	2.1
2846	1%" and 17/16"	17%"	2.4
2852	11/2" and 11/4"	191/2"	3.8

6 piece OPEN END WRENCH SET



Includes Nos. 2812, 2816, 2820, 2825, 2829, and 2832.

No. 2800-8 Open End Wrench Set in No. 2428 Kit Wt. 2.5 lbs.

WORLD'S MOST BEAUTIFUL TOOLS

P & C tools are not only the best in quality, but they are the best in feel, balance and appearance.

OPEN END WRENCHES



Special alloy steel gives extra strength to very thin, tapered jaws. Long handles keep hands away from hot manifolds, increase leverage.

No.	Opening Sizes	Length	Wt. Lbs.
2916	7/16" and 1/2"	9"	.18
2918	1/2" and 9/16"	9"	.18


PED MIDGET WRENCHES



One jaw at 15°, other at 60° on each wrench. Opening sizes duplicated at other angle on companion wrench.

				Wt.
No.	15° End	60° End	Length	Lbs
130	13/64"	15/64"	3"	.02
131	15/64"	13/64"	34	.02
132	7/32"	1/4"	3"	.02
133	1/4"	7/32"	3"	.02
134	9/32"	5/16"	31/4"	.03
135	5/16~	9/32"	314"	.03
136	11/32"	3/8"	33/4"	.05
137	3/8"	11/32"	3%4"	.05

MIDGET WRENCH SET



Eight wrenches from $^{1}\%4''$ to %'' jaw openings in both 15° and 60° angles plus No. 1235 Midget Pliers.

No. 140-D Midget Wrench Set Wt. .60 lbs.

PER BOX WRENCHES

Thin walls provide extra clearance. Special alloy steel has high tensile strength. Box openings chamfered to guide wrench onto nut, bolt heads. Once on, it cannot slip or spread, needs only 15° swing to turn a nut. Heads offset 15° from shank to provide knuckle clearance. Heavily chrome plated all over to resist rust.

FLAT HANDLED SERIES

0	1/15 @ 2510		A CO
No.	Opening Size	Length	Wt. Lbs.
2512	516" and 3/8"	6"	.1
2514	%" and 7/10"	61/2"	.1
2516	7/16" and 1/2"	3"	.15
2518	1/2" and 9/16"	8"	.2
2520	%16" and %"	81/4"	.25
2522	%" and 11/16"	91/4"	.6
2524	5/8" and 3/4"	91/2"	.6
2525	11/16" and 3/4"	111/4"	.7
2526	%" and %"	131/4"	.8

ROUND HANDLED SERIES

1514"

1734"

1310" and %" 1516" and 1" 1516" and 1%"

2532

2536

2234	%" and 11/10"	16"	1.33
2240	11/10" and 11/4"	19"	2.33
2242	14" and 11/18"	19"	2.40
2244	14" and 1%"	19"	2.45
2246	11/4" and 17/4"	191/4"	2.60
2248	13/10" and 11/2"	20"	3.50
2250	17/16" and 1%"	22"	3.80
2264	1184 -# and 9#	253/. //	8 20


6 piece BOX WRENCH Set



Includes Nos. 2514, 2518, 2522, 2528, 2529, and 2532.

No. 2500-B Box Wrench Set Wt. 3,3 lbs.

VINYL PLASTIC FLEXIBLE KITS FOR TOOL SETS



Vinyl plastic kits offer many advantages for storing and carrying tools. They have amazing durability and are noted for long wear. They are flexible, won't crack or peel, are scratch and scuff proof, resists oil and grease, and are easy to clean with soap and water.

The kits are blue with white marking, and they retain their new, handsome appearance. They have strongly stitched seams and heavy tie strings.

The flaps are just a little longer than the tools they are designed for, eliminating fold-under flap objection but offering protection to and from sharp tools.

Combination Wrench Set in No. 2413 Kit Wt. 10 lbs.

			AA I' TITE
2401	23 pockets	8" x 251/2"	.44
2409	3 pockets	6¾" x 3¼"	.03
2413	15 pockets	25" x 181/2"	.58
2416	9 pockets	8346" x 5%"	.09
2425	6 pockets	17%" x 10%"	.25
2427	6 pockets	10%" x 9%"	.15
2428	6 pockets	13" × 11%"	.22

Page 7

BOX WRENCHES

Sturdy and yet light in weight for easiest and longest use. All over chrome prevents rust and makes cleaning easy. Requires only 20 degrees of arc for continuous ratcheting.



		TAbe		
	and the second second	of (Over-	
	Opening	Open-	all	Wt
No.	Size	ing I	ength	lbs.
1191	$1/4" \times 5/16"$	6-point		.12
1192	3/8" x 7/16"	6-point	51/4"	.20
1193	1/2" x 9/16"	6-point	634"	.40
1194	5/8" x 11/16"	12-point	844	.66
1195	3/4" x 7/8"	12-point	91/4"	.79
1196	5/8" x 3/4"	12-point	81/16"	.64



ATTACHMENTS AND SETS

Sockets hot broached from special alloy steel, precision machined for precise, accurate fit. Light, thin-walled, extremely tough and long wearing. Chamfered openings slip on nuts and bolt heads easily. Heavy chrome plate resists rust, wipes clean instantly. Square drive openings receive same accurate machining for positive drive and fit. Sizes plainly, permanently marked on each socket. Attachments for Sockets skillfully designed, accurately forged from same strong alloy steel. Square drives precisely machined for accurate fit; knurled handles insure easy, positive grip; each attachment scientifically balanced. Friction ball on all square drive attachments holds socket securely-it can't slip or drop off.

ATTACHMENTS AND SETS

Designed to withstand the toughest demands of light to medium jobs. Ideal for Ignition, Carburetor, Radio, or T-V assembly, maintenance and repair.



6 point SOCKETS (All 1" in length)

No.	Size	Wt.	No.	Size	Wt. lbs.
0206	3/16"	.02	0210	5/16"	.03
0207	7/32"	.02	0211	11/32"	.03
0208	1/4"	.02	0212	3/8"	.04
0209	9/32"	.03	0214	7/16"	.05

8 point SOCKETS

No.	Size	Length	Wt. lbs
0208-5	1/4"	1"	.02
0210-5	5/16"	In	.04
0212-5	3/6"	1"	.05

12 point SOCKET

No. 0216 Size 1/2" Length 1" Wt. .05 lbs.

SLIDING T-HANDLE



No. 0253 Length 41/2" Wt. .08 lbs.

SPINNER HANDLE



No. 0259 Length 5%" Wt. .13 lbs.

HINGE HANDLE



No. 0251 Length 51/16" Wt. .16 lbs.

UNIVERSAL JOINT



No. 0252 Length 17/12" Wt. .03 lbs.

EXTENSIONS



No. 0247	Length 3½"	Wt06 lbs.
0248	6"	.10
0263	14"	.10

SPEEDER HANDLE



No. 0280 Length 16" Wt. .40 lbs.

REVERSIBLE RATCHET



Ratchet wheel has 30 teeth to turn socket continuously with only 12° arc. Compact, chrome plated, ideal for small to medium jobs.

No. Length Head Thickness Wt. lbs. 0246 4½" 3/8" .18

SCREWDRIVERS



No.	Bit Size I	ength	Wt. lbs
0237	Phillips No. 1	1"	.02
0238	Phillips No. 2	1"	.02
0237L	Phillips No. 1	2"	.03
0238L	Phillips No. 2	2"	.03
0244	3/16" x .030"	1341	.03
0245	1/4" x .030"	3"	.06


ADAPTORS



No. 0271 Length 15/16" Wt. .05 lbs. Adapts %" drive attachments to ¼" drive sockets.

No. 0272 Length 15/16" Wt. .03 lbs. Adapts ¼" drive attachments to %" drive sockets.

PED 1/4" DRIVE SETS



12 piece 4" DRIVE SET

Op	ening Size	- 0	pening Size
	6-point		8-point
No.	sockets	No.	sockets
0207	7/32"	02085	1/4"
0208	1/4"	02105	5/16"
0209	9/32"		
0210	5/16"	0259	Spinner Handle
0211	11/32"	0253	Sliding T-Handle
0212	3/8"	4795	1"x21/4"x61/4"
0214	7/16"		Metal Box

No. 0200-A 12-piece Socket Set, Wt. 1 lb.

13 piece 1/4" DRIVE SET



Opening Size		Opening Size		
	6-point		8-point	
No.	sockets	No.	sockets	
0207	7/32"	02085	1/4"	
0208	1/4"	02105	5/16"	
0209	9/32"	0246	Reversible	
			Ratchet	
0210	5/16"	0259	Spinner Handle	
0211	11/32"	0253	Sliding T-Handle	
0212	3/8"	4795	1"x21/4"x63/4"	
0214	7/16"		Metal Box	

No. 0200-C 13-piece Socket Set Wt. 1.16 lbs.

16 piece 1/4" DRIVE SET

0	pening Siz	e Or	ening Size		
	6-point		8-point		
No.	Sockets	No.	Sockets		
0206	3/16"	02085	1/4"		
0207	7/32"	02105	5/16"		
0208	1/4"	02125	3/8"		
0209	9/32"	0251	Hinge Handle		
0210	5/16"	0246	Ratchet		
0211	11/32"	0247	34" Extension		
0212	3/8"	0248	6"		
0214	7/16"	4795	1"x21/4"x63/4"		
No. 0200-F 16-piece Socket Set					
2100	200-1 20 P.		Wt. 19 lbs.		

Pac W DRIVE SOCKETS ATTACHMENTS AND SETS

SOCKETS



		Opening	ž	Wt.
	No.	Size	Length	lbs.
Square*—	3009-5	9/32"	15/16"	.04
6 point Hex-	-3010-H	5/16"	1"	.04
	3012-H	3/8**	1"	.04
	3014-H	7/16"	1"	.04
	3016-H	1/2"	1"	04
	3018-H	9/16"	1"	.05
	3020-H	5/8"	1"	.07
	3022-H	11/16"	11/16"	.10
12 point—	3012	3/8"	1"	.04
	3014	7/16"	1"	.04
	3016	1/2"	1"	.04
	3018	9/16"	1"	.05
	3020	5/8*	1"	.07
	3022	11/16"	11/16"	10
	3024	3/4"	11/18"	13
	3026	13/16"	13/16"	15
	3028	7/8"	13/16"	.17

*Fits drain plug on Dynaflow torque converter.

EXTRA DEEP



12 point -	3112	3/8**	21/6"	.10
	3114	7/16"	21/6"	.10
	3116	1/2"	21/6"	.10
	3118	9/16"	21/6"	.12
	3120	5/8"	21/4"	.15
	3122	11/16"	23/4"	.18
	3124	3/47	21/5"	_20
	2124	13/16*	284#	20

SPECIAL SPARK PLUG SOCKET





-tnion 8

3126-HP 13/16" 27/16" .28 3126-R Insert for 3126-HP and 6126-HP

UNIVERSAL



		Opening		WL
	No.	Size	Lengtl	h lbs
12 point—	3312	3/8"	11/2"	.10
	3314	7 16"	11/2"	.10
	3316	1 2"	11/2"	.10
	3318	9 - 16"	19 105	.10
	3320	5, 8"	134"	.12
	3322	11/16"	1%"	.12
	3324	3/4"	2"	.15

REVERSIBLE RATCHET



New, sturdier, compact design features a smaller head and fewer moving parts. Advancing and reversing ac-complished with one dog Enclosed head is simple and easy to disassemble for cleaning or replacing worn parts when necessary.

No. 3209 Length 71/4" Wt. .50 lbs.


REPLACEMENT PARTS KIT



Contains all parts for 3/4" Drive Reversible Ratchet No. 3209. Includes one each: Wheel, Dog, Keeper Ring, Plug Drive Ring.


No. x-3209 Wt. .09 lbs. For individual parts see price list

HINGE HANDLE




No. 3230 Length 71/2" Wt. .35 lbs


SPEEDER HANDLE



SLIDING T-HANDLE



EXTENSIONS



No.	3202	Overall	length	31/4"	Wt.	.13	lbs
	3203			8"		,25	
	3205		1	121/2"		.38	
	3206		1	181/2"		.55	

UNIVERSAL JOINT



No. 3208 Length 13/4" Wt. .10 lbs

SCREWDRIVER



Bit 5/16" Length 21/2" No. 3211 Wt. .08 lbs.

Page 9

ADAPTORS



No. 3071 Length 1%" Diam. 13-16" Wt. .13 lbs. Adapts ½" drive attachments to %" drive sockets

No. 3072 Length 11/8" Diam. 3/4" Wt .10 lbs Adapts %" drive attachments to 12" drive sockets.

10 piece "BASIC" 34" DRIVE SET



No.	Openi	ng Size	No	
3012	3/8"	12 point	3202	3" Extension
	7/16"		3209	Reversible
3016	1/2"			Ratchet
3018	9 16"		3230	Flex Handle
3020	5 8"		5295	Metal Box.
3022	11 16"			1846"x534"
3024	3/4"			x1½"

No. 3000-NR 10-Piece Basic Set Wt. 3.72 lbs

3000-CR Same as No. 3000-NR except in durable cardboard box, makes attractive gift package. Wt. 1.8 lbs.

14 piece "UTILITY" %" DRIVE SET



*49.	- 4		-	-	
No.	Openi	ng Si	ze	No	
3012	3/8"	12 p	omt	3209	Reversible
					Ratchet
	7/16"			3202	3" Extension
3016	1/2"			3203	8" Extension
3018	9, 16"			3230	71/2" Flex
					Handle
3020	5/8"			3208	Universal
					Joint
3022	11/16"			3215	18" Speeder
					Handle
3024	3/4"			5295	Metal Box.
					18 "x514"

3000-K 14-Piece Utility Set Wt. 4.9 lbs.

MONE MASTER CRAFTSMEN

are using P & C Tools today than ever before. Electricians, plumbers, mechanics and hobbyists recommend P & C Tools.

P&D...the best tools money can buy...

45 piece "MASTER" %" DRIVE SET



Opening

Opening

No.	Size	390.	Bize
3009-5	9/32" Sq		
	6 F	oint	
		3018-H	9 /15#
3010-H	3/8"	3020-H	
3012-H		3020-H	
3014-H		3022-11	44/ 10
3016-H			
		Point	
3012	3/8"	3022	11/16"
3014	7 16"	3024	3/4"
3016	1/2"	3026	13/16"
3018	9/16"	3028	7/8"
3020	5/8"		
	Extra De	ep 12 Po	oint
3114	7/16"	3209	Reversible
3116	1/2"		ratchet
3118	9/16"	3230	7½" hinge
3120	5/8"		handle
3122	11/16"	3241	Screw-
3124	3/4"		driver
3126	13/16"		*2 Phillips
3126-H	P13/16" Spk.	3242	Screw-
	plug		driver
3202	3" Ext'n		#3 Phillips
3203	8" Ext'n	3243	Screw-
3205	12½" Ext'n		driver
3206	181/2" Ext'n		*4 Phillips
3208	Universal		
	joint		
	12 Point Uni	versal S	Sockets
3312	3/8"	3320	5/8"
3314	7/16"	3322	11/16"
3316	1/2"	3324	3/4"
3318	9, 16"		
3215	18" Speede	r 5495	Box-Metal
	handle		box, 191/2"x
3260	71/2" Slidin	g	8¼"x1¾"
	T-		



handle No. 3000-F 45-piece Master 1/8" Drive

SOCKETS



12 pc	int (for use on	hex bolts	or nuts)
No.	Opening Size	Length	Wt. lbs
6012	3/8*	1%"	10
6014	7/16"	1%"	.10
6016	1/2"	1%"	.10
6018	9/16"	184 *	10

6019	19/32**	1%**	.13
6020	5/8**	1%"	.13
6021	21/32~	1%"	.13
6022	11/16"	136"	.13
6024	3/4"	1%″	.15
6025	25/32"	1%"	.18
6026	13, 16~	1%"	.20
6028	7/8"	1%"	,23
6029	29/32*	1%"	.25
6030	15/16"	11/4"	.28
6031	31/32~	11/2"	.28
6032	1"	11/2"	.33
6034	11/10"	195ս"	.38
6036	156"	1%"	.04
6038	13/16"	111/16"	.45
6040	1%"	134"	.65

12 point EXTRA DEEP



	Opening Size	Length	Wt. 1b
6116	1/2"	31/4"	.23
6118	9/16"	31/4"	,23
6120	5/8"	31/4"	.23
6122	11/16"	31/4"	.25
6124	3/4"	31/4"	.30
6126	13/16"	31/4"	,35
6128	7/8"	31/4"	.43
6130	15/16**	31/4"	.45
6132	1"	3¼"	.50
6134	11/10"	314"	.63
6136		31/4"	.65

SPECIAL SPARK PLUG SOCKET

(See illustration page 9.) 6126-MP 13/16" 3¼" .35

8 point (for use on square bolts or nuts)



No.	Opening Size	Length	Wt. 1b
6082	3/8"	1%"	.13
6084	7/16"	1%"	.13
6086	1/2"	1%"	.13
6088	9/16"	1%"	.18
6090	5/8"	17/10"	.18
6092	11/16"	11/2"	.25
6094	3/4"	19/16"	.36
6096	13/16"	19;6"	,39
6098	7/8"	19/16"	.45

REVERSIBLE RATCHET



One dog controls motion, advancing or reversing. Finger-tip lever control convenient, easy to operate. Thirty teeth on wheel allow continuous turning in only 12° arc. Double-edge dog prevents slipping, even under heavy use. Enclosed head quickly and simply disassembled for cleaning or replacing worn or broken parts if necessary.

No. 6211 Length 10¼" Wt. 1.2 lbs. No. 6212 Length 16" Wt. 1.8 lbs.

HINGE HANDLES



No. 6230 Length 11" Wt. 1.08 lbs. No. 6235 Length 15" Wt. 1.56 lbs. No. 6238 Length 18" Wt. 1.7 lbs

REPLACEMENT PARTS KIT



Contains all parts for 1/2" drive Reversible Ratchet No. 6211 and 6212. Includes one each. Wheel, Dog, Keeper Ring, Plug Drive Ring.

No. X-6211 Wt. .09 lbs. For individual parts see price list

SLIDING T-HANDLE




No. 6265 Head 1%" Bar 15" Wt. 1.3 lbs

SPEEDER HANDLE



No. 6215 Shank Length 8" Length 181/2" Swing 4" Wt. 1.43 lbs.

EXTENSIONS



UNIVERSAL JOINT



No. 6208 Length 2)/16" Wt. .23 lbs.

ADAPTORS



No. 6071 Length 11/4" Wt. .33 lbs. Adapts 1/4" drive attachments to 1/2" drive sockets.

No 6072 Length 19/16" Wt. 25 lbs. Adapts '4" drive attachments to 34" drive sockets.

DRAG LINK ADJUSTER



No. 6076 Length 1%" Wt. .25 lbs. Blade .150" thick, 15/16" wide.

RATCHETOR



Converts any ½" drive attachment into reversing racheting device. Simple mechanism, compact, strong. No. 6247 Wt. .73 lbs.

Page 10



14 piece "BASIC" 1/2" DRIVE SET



	Socket		Socket
No.	Size	No.	Size
6014	7/16"	6024	3/4"
6016	1, 2"	6026	13 16"
6018	9 16"	6028	7/8"
6020	5 8"	6030	15, 16"
6022	11/16"	6032	1"
No			
6211	Ratchet		
6238	18" Flex	Handle	
6201	5" Extens		
5495	Metal Bo		8¼"x1¾"
0 4000	NB Mari	ann hans	16r The

No. 6000-NR 14-piece basic 1/2" Drive Set. Wt. 10.7 lbs

No. 6000-CR Same tool selection as No. 6000-NR in heavy, three-color cardboard box, very serviceable, makes ideal gift carton. Wt. 6.8 lbs.

17 piece "STANDARD" '½" DRIVE SET



No	Socket Size	No	Socket Size
6014 6016 6018 6020 6022 6024	7/16" 1 2" 9 16" 5 8" 11 16" 3, 4"	6026 6030 6032 6203 6205	13 16" 7 '8" 15/16" 1" 5" Ext 10" Ext
No. 6208 6211 6215 6238	Universal Ratchet 18" Speed Flex Hand Metal Box	er ile	k 1/4 // no 1 3/4 //
6215	18" Speed	dle	3¼"x1¾"

No. 6000-K 17-piece standard 1/2" Drive Set Wt. 13 lbs


12 piece EXTRA DEEP 1/4" DRIVE SOCKET SET



	Opening		Opening
No.	Size	No.	Size
6116	1/2"	6128	7/8"
6118	9/16**	6130	15/16"
6120	5/8"	6132	1"
6122	11/16"	6134	11/16"
6124	3/4"	6136	114"
6126	13/16"		

No. 6109-A 12-piece Extra Deep 1/2" Drive Socket. Set in Cardboard Carton. Wt. 4.75 lbs. Set includes

55 piece "MASTER" 1/2" DRIVE SET



Wt. ?? 1
0
Opening Size
29 32"
15/16"
31 /32"
1"
11,10"
148"
V110"
11/4"
Drag link
adjuster
11/16"
3/47
13 16"
7/8"
Inanina

	Opening		Opening
No,	Size	No.	Size
	Extra De	ep 12 P	oint
6116	1/2"	6126-F	P13/16" Spk.
6118	9/16"		plug
6120	5/8"	6128	7/8"
6122	11/16"	6130	15/16"
6124	3/4"	6132	1"
6126	13/167	6134	13/16"
		6136	11/4"
6202	21/2" Ext'n	6215	18" Speeder
6203	5" Ext'n	6230	11" Hinge
4205	10" Ext'n		handle
6206	18" Ext'n	6235	15" Hinge
620B	Universal		handle
	joint	6238	181/4" Hinge
6211	101/4" Re-		handle
	versible	6265	Shding
	ratchet		T-handle
6212	16" Re-	9971	19"x7"x8¾"
	versible		Hip roof
	ratchet		tool box

No. **6000-F** 55-piece master ½" Drive Set. Wt. 32 lbs.

ATTACHMENTS AND SETS



12 POINT SOCKETS						
	Opening	Inside				
No,	Size	Clearance	Length	Wt. Ibs		
9326	7/8"	11/2"	2"	.35		
9330	15 16"	118"	2"	40		
9332	1"	11 _g "	2"	43		
9334	11,7"	118"	2"	48		
9336	118"	114"	21/8"	53		
9338	1000	154"	21.n"	58		
9340	114"	154"	2487	70		
9342	1" ,"	114"	21/6"	70		
9344	13/8"	138"	244"	73		
9346	17 ,6"	13 _B "	21,4"	.80		
9348	1142"	138"	214"	85		
9350	19 6"	11/2"	24,"	90		
9352	15g"	112"	238"	1 05		
9356	134"	134"	242"	1 45		
9358	11316"	17a"	25%"	1 80		
9360	17a"	I'a"	25,5"	1 90		
9364	2"	2"	224"	2 13		
9368	21,"	2"	23.,"	2 45		

HINGE HANDLE



No. 9238 Length 20" Wt. 3.2 lbs.

L-HANDLE



No. 9255 Length 1712" Wt. 2.35 lbs

SLIDING T-HANDLE



No. 9265 Head 24" Bar 18" Wt. 2.73 lbs.

EXTENSIONS



No. 9203 Overall length 5" Wt. 1.05 lbs. 9204 8" 1.43 9206 16" 2.30

REVERSIBLE RATCHET



Twenty inches long, it has ample leverage and power for tough jobs Extra heavy, sharp teeth on dog and wheel assure positive action under rugged use. Operates in an arc of only 20° and its small, compact head gets into tight corners. Finger tip control on single dog reverses direction quickly No. 9209 Length 20° Wt. 4.0 lbs.

REPLACEMENT PARTS KIT



Contains all parts for ¼" Drive Reversible Ratchet No. 9209 Includes one each: Wheel, Dog, Keeper Ring, Plug Drive Ring for a single Ratchet.

No. X-9209 Wt. .6 lbs. For individual parts see price list

E... the best tools money can buy...

UNIVERSAL JOINT



No. 9208 Length 334" Wt. 1.0 lbs.

ADAPTORS




No. 9071 Length 21/2" Wt. 1.10 lbs. Adapts 1" drive attachments to %" drive sockets.

No. 9072 Length 24" Wt. 58 lbs. Adapts 4" drive attachments to 1" drave sockets.

DEO %" DRIVE SI

12 piece "BASIC" 34" DRIVE SET



9334	11/16"	9356	13,4
9336			Sliding T-Handle
9340			8" Extension
	13/10"		20" Reversible
POTA	471G	7207	Ratchet
	174		Natchel

9348 13/2" 5695 4"x4"x21" Metal Box

9352 1%"

No. 9300-NR 12-piece Basic %" Drive Set Wt. 19.7 lbs.

28" piece "MASTER" W" DRIVE SET



No.	Size	No.	Size	No.	Size
9328	7/8"	9342	1346"	9354	111/18"
9330	15/16"	9344	1%"	9356	13/4"
9332	1"	9346	17/10"	9358	10346"
9334	11/16"	9348	11/2"	9360	17/5"
9336	1%"	9350	1910"	9364	2"
9338	13/10"	9352	1%"	9368	21/8"
9340	1%"				
	En Deck.				

9203 Extension 9204 8" Extension 9206 16" Extension 9208 Universal Joint

Reversible Ratchet Flex Handle 9209

9238 L-Handle 9255

Sliding T-Handle 9265 30"x81/4"x5" Metal Box 5696 28-piece Master 3/4" Drive

No. 9300-F Set. Wt. 55 lbs.

PaB I" DRIVE SOCKETS ATTACHMENTS AND SETS

12 point SOCKETS



	Opening	Inside		Wt
No.	Size	Clearance	Length	lbs.
9552	1%"	244"	31/4"	1.73
9558	113/16"	2546"	33/10"	1.85
9560	400	2%"	3%"	1.94
9564	2"	27/10"	37/10"	2.2
9570	2340"	2%	334"	3.1
9572	21/4"	21316"	313/16"	3.4
9576	2%"	215/16"	313/16"	3.9
9580	21/2"	3"	4"	4.6
9582	2946"	3"	4"	4.9
9584	2%"	31/6"	41/6"	5.2
9588	234"	3%"	4%"	6.2
9594	21716"	31/4"	45%"	7.7
9596		31/4"	456"	7.9
9600	31/6"	31/8"	47'B"	9.6
9612	31/4"	41/4"	51/2"	15.0

REVERSIBLE RATCHET



Exceptionally strong with extra steel at points of stress. Enclosed head design with convenient reversing lever. Removable drive plug has non-slip friction ball to hold sockets and extensions securely, Over-all length 26".

No. 9509 Length 28" Wt. 12.0 lbs.

SLIDING HEAD



No. 9565 Length 3" Wt. 1.48 lbs.

EXTENSIONS




No. 9504 Length 9" Wt. 3.6 lbs. 9504 18" 6.0

CROSS BAR

No. 9501 Diam. 1" Length 24" Wt. 5.3 lbs.

1" DRIVE SET 10 piece "HEAVY DUTY" SET



No 114'16" Socket 9558 9564

2" Socket 2%" Socket 2%" Socket 9570 9576 23/4" Socket

9588 Reversible Ratchet 9509

9504 9" Extension 9501 Cross Bar

9565 Sliding Head for No. 9501 5894 Metal Box 30"x81/4"x5"

No. 9500-OC Set Wt. 60 lbs.

PLUMBING FOOLS

Highest quality alloy chisel steel. Large, octagon handles with beveled heads designed to give perfect balance and positive grip. All calkers, floor chisels, and yerning irons have substantially offset handles for safe knuckle clearance. Service ends highly polyshed lacouer dinned to resist ly polished, lacquer dipped to resist rust. Edges are oil tempered to retain sharpness.

Pag CUTTING TOOLS

STAR DRILLS

No.	Stock Size	Width of Cut	Length	Wt.
13%	1/4"	1/4"	12"	.17
13918	1/4"	5/16"	12"	.17
13%	5/16"	3/8"	12"	.26
131/2	3/8"	1/2"	12"	.39
13%	7/16~	5/8*	12"	.53
13%	1/2"	3/4"	12"	.85
13%	5/8"	7/8"	12"	1.06
13-1	3/4"	1"	12"	1.56

CONCRETE GADS

No. Stock Size Wt. lbs. Length 3/4" 7/8" 84% 12" 1.42 12" 84% 1.84 84-1 12" 2.40

FLOOR CHISELS



SOIL PIPE CHISELS



P&C TOOLS . . . Sold All Over The World

P & C Tools are displayed and sold In every state in the union and in many foreign countries. Craftsmen and mechanics the world over who appreciate good tools, buy P & C. You can buy them with confidence



OFFSET YARNING IRONS



SPRING YARNING IRONS

WATER MAIN CALKER



No.	Stock Blade Size Thickness	Blade Width	Lgth lbs.
107%	13/16" 3/8"	11,16"	8" .85
1071/2	13/16" 1/2"	15/10"	81/4" .87
	Stock Blade	Blade	Wt.
No.	Size Thickness	Lgth.	Lgth, lbs
109	3/4" 3/16"	211/16"	88. "8

LONG CALKERS



LONG GASKET CALKERS



BROAD CURVED NOSE CALKER



OFFSET CALKERS



0331/2 Out 1/2"	3/4"	155"	65'a"	.30
	= -		,	-00
033% in 5/8"	7/8"	1%"	71/8"	49
033% Out 5/8"	7 '8"	156"	7344	.49
034% In 5/8"	23 32"	1716"	7"	.47
034% Out 5/8"	23. 32"	15,16"	7"	47

CURVED PONY CALKERS



	Stock	Blade			Wι
No.	Size	Width	Length	Length	lbs
21 ½ fn	1/2"	3/4"	114"	3"	.14
211/2 Out	1/2"	3/4"	144"	3"	.14

CEILING CALKER




Blade Blade Overall Wt Width Length Length lbs 11/16" 1%" 10" 1,20

LEFT AND RIGHT CALKERS



	Stock	Blade	Blade	Overall	Wt.
No.	Stock Size	Width	Length	Length	lbs.
132L	5/8"	7/8**	15%"	Length 81/8."	.87
132R	5/8"	7/8"	196"	876"	.87

LEAD PICKING TOOL



BENDING IRONS

		0		
No. 135½ 135%	Stock Slze 1/2" 5/8"	Overall Length 10%" 10%"	Wt. lbs. .50 .75	

TUBING EXPANDER



This special tool expands pipe or tubing in three steps to inside diameters of 1¼", 1%" and 1½".

No. 1261/2 Length 31/2" Wt. ,86 lbs.

INTERNAL PIPE WRENCH




Dogs grip securely inside pipe. Easily removed with little injury or distortion A must for plated fittings.

No.	Pipe Size	Length	Wt. lbs.
140	1/2"	31/2"	.5
141	3/4"	394"	.8
142	Į"	4"	.95

PAG PULLERS

HEAVY DUTY PULLER



Designed and built to handle heaviest jobs. Detachable tip on screw remains stationary, does not score surfaces.

Quan	. No.	Description
2	4011	Crossarm 11" long.
1	4012	Screw, 111/4" long; 1/4" hex
		head with 4012-7 Detach-

able Tip—60° taper.

Jaws, 4%" from crossarm 4015 to hook.

4016 Jaws, 7" from crossarm to hook

Timing Gear Jaws, 7" from crossarm to hook.

2 4018 Cap Screw Jaws, 3" from crossarm to hook.

Heavy Duty Set, as listed above, in 4019 Steel Box, 1½"x5½"x12". Wt. 14.4 lbs. Heavy Duty Set without box. Wt. 12.6 lbs. Set 4030-A

Set 4030-8

Set 4010-B Heavy Duty Set, with two sets of jaws. Includes: 4011 crossarm; 4012 screw; 2 each 4015 4%" jaws; 2 each 4016 7" jaws.

Also available.

4011-8 Spring for Jaws 4015, 4016, 4017, 4018.

MEDIUM DUTY PULLER



Ideal for generators, starter and armature gears, bearings, cones, ball races, and many similar jobs. Strong forged jaws adjust quickly, easily. Tip of screw is detachable and does not rotate. Prevents scoring expensive shafts. Screw stays on center under pressure without "walking" on flat surfaces.

Quan.	No.	Description
	4021	Crossarm, 7" long.
4	4021-8	Spring for Jaws.

Screw, ?" long: ½" hex head with 4022-7 Detach-able Tip-60" taper. Jaws, 2" from crossarm to 4022

hook.

Jaws, 4" from crossarm to book.

P&C...the best tools money can buy...

Medium Duty Set in 4029 No. 4020-A Steel box, 14"x34"x74"

Wt. 4.1 lbs

No. 4020-B Medium Duty Set as listed without box. Wt. 3.2 lbs. No. 4020-C Medium Duty Set consist-

ing of 1 4056-C, 1 4022, 2

4028. Also available

1 4022-75 Small diameter tip for

4027 Narrow Jaw, 4" from crossarm to hook

4028 3" Cap Screw.

MORE MASTER CRAFTSMEN

are using P & C Tools taday than ever before. Electricions, plumbers, mechanics and hobbyists recommend P & C Tools

THREE-JAW LIGHT DUTY PULLER



(Similar to 4060-A, except it has 3 jaws)

Quan. No. Description

Screw, 634" long, 1/4" hex head with 4022-1 Detach-4022 able Tip.

Knurled non-reversible

adjusting nut, 1%" diam
4071 Yoke, 2%" diam., for hold-

ing 3 jaws.
3 4056-PN Pins with ball check to hold jaws in yoke.

Outside jaws, 41/2" long, 0" to 3" range.

No. 4070-C Light Duty Set. Wt. 1.94 lbs. as listed above.

TWO-JAW LIGHT DUTY PULLER



Narrow jaws on this tool need little space. Ideal for smell gears, pulleys, bearings. Adjusting nut holds jaws firmly in position so they cannot slip. Quan. No. Description

4022 Screw, 6%" long, %" hex head with 4022-7 Detachable Tip.

Knurled non-reversible adjusting nut, 1%" diam. Yoke, 2%" wide, for hold-

ing two jaws.
4056-PN Pins with ball check to

hold jaws in Yoke.

Reversible Jaws, 31/4" long, 0" to 11/4" range. Outside Jaws, 41/2" long, 0"

to 3" range. No. 4060-A Light Duty Set. Wt. 175 lbs. as listed above.

SLIDE HAMMER PULLER

Axles, bearing cups, sleeves, retainers and other stubborn parts are handled effectively under the impact of this 2½ lb. sliding hammer

Quan, No. Description

1 4056-R T-Handle Rod, 24" long,

threaded end 1 4056-H 2½ lb. Sliding Hammer with fluted grip.

Knurled Reversible Adjusting nut, 2½" diam. Yoke for holding 3 jaws, 1 4056-N

21/2" diam.

4056-J Reversible Jaws, 31/2" long. 4056-PN Pins, with spring ball check to hold jaws in yoke.

No. 4056 Slide Hammer Set, Wt. 6.1 lbs No. 4056-A Pilot Bearing Puller Set. In-

4056-R5 Short Rod, 4056-H Hammer; 4056-N Nut; 4061 2½" wide yoke; 2 each 4056-PN pins; 2 each 4058-J reversible jaws. Wt. 4.9 lbs.

Also available

4056-R\$ Short slide hammer rod, 12%" long. Wt. 96 lbs.

4057-J Long Reversible Jaws, 45%". Wt. .18 lbs.
4058-J 3952" Inside Jaw for Pilot Bearings. Wt. 10 lbs.

UNIVERSAL WHEEL PULLER



Fast, simple, this puller handles wheels of practically every car or truck. Legs adjust quickly to any drum with 3, 4, 5, 6, or 7 studs in a circle up to 61/2' diameter. Legs take studs up to %16 Supplied with Adaptor Ring and Screws shown for Ford wheels

No. 4001 Puller includes:

Quan. No. Description

1 4001-8 Puller Body, 64" long. 4001-5 1" Puller Screw, with detachable tip 4001-578" long

Legs, offset 15/18" to clear hubs; 3%" from Crossarm 4001-J to offset.

4001-R Ford Adaptor Ring. Ford Adaptor Cap Screws, 41/2" long.

No. 4001 Universal Wheel Puller, Wt.

No. 4000-D Universal Wheel Puller without Ford Adapter Screws and ring. Includes: 4001-8 Puller body; 3 each 4001-J Legs; 4001-S Puller screw. Wt.

Also available: 4001-II. Legs, offset 13/4" to clear hubs; 3%" from Crossarm to offset.

STEERING WHEEL PULLER



Ideal for many cap screw pulling jobs, this puller is designed for drilled and tapped steering wheels. Holds two diametrically opposed cap screws, or three screws spaced 120° spart. Rotating screw tip is cut away to prevent interference with horn button wiring. No. 4043 Steering Wheel Puller Set. Wt. 1.03 lbs.

Parts: 4043-B body, 4043-S screw with tip, 4043-T tip only

BATTERY TERMINAL PULLER



Different from conventional pullers, this type is lighter, easier to use and faster to set up.


> No 4042 Wt. 44 lbs.

BATTERY TERMINAL PULLER



Removes battery terminal clamps quickly and easily, even when badly corroded. Handy for small bearings and other light pulling jobs. No. 4041 Length 44" Wt. .65 lbs.

BEARING SEPARATOR AND PULLER ATTACHMENT



Designed to work in limited space, thin, sharp edges and flat surfaces make adjustments easy, protect expensive bearing.

No. 4032 Bearing Separator and Puller Attachment Set. Maximum opening 4½", width 5114". Wt. 4.4 lbs.

Parts: 4032-A top plate, 4032-B bottom plate, 4032-5 bolt and nut



Used as base for puller screw on hollow shafts and housings when pulling bushings, gears, etc. Handy for installing oil seals.

_	Small	Large	
No.	Diam.	Diam.	Wt. lbs.
4040-1	3/4"	1"	.05
4040-2	7/8*	11/6"	80.
4040-3	1"	11/4"	.10
4040-4	11,5"	136"	.13
4040-5	11/4"	1%"	.19
4040-6	1%"	1%/*	,22
4040-7	11/2"	1%"	.28
4040-8	1%"	2"	.33
4040-9	134"	21/e"	.40
4040-10	1%"	2%"	.49
4040-11	2"	21/5"	.59
4040-12	214"	25%**	.65
4040-13	21/4"	23/4"	.76
4040-14	2%"	21/5"	.83

No. 4040 11 piece Step Plate Set Wt. 3.0 lbs. Includes Nos. 4040-1 to 4040-11

AUXILIARY PULLER PAG ATTACHMENTS

They all are interchangeable with the 4056 SLIDE HAMMER PULLER and the 4060-A and 4070-C LIGHT DUTY PULLER SETS

DEEP SLOTTED CAP SCREW CROSSARM



Ideal for pulling gears, pulleys and other assemblies with cap screws. Slots take up to 7/16'' bolts between arms

No. 4056-C Length 6" Wt. 1.10 lbs.

COLLET TYPE BLIND BEARING PULLER



Exceptionally wide shoulder expansion adapts it to many applications in addition to pulling fly-wheel pilot bearings. Hex head %4" tapped for No. 4022 screw and 4056-R Slide Hammer T-Rod handle. No. 4080 Length 4½" Wt. .34 lbs.

INSIDE JAW



Increases range of Light Duty Pullers in many inside pulling jobs. No. 4056-L Length 4½" Wt. .21 lbs.

SINGLE JAW



Fast and convenient for wheel alignment and brake work. Pulls grease retainers in small shafts, bearings, bushings, etc

No. 4056-S Length 215/16" Wt. .17 lbs.

LONG OUTSIDE JAW



Increases range of light duty pullers on many outside pulling jobs.

No. 4067 Length 72332" Wt. 30 lbs.

WEDGE TYPE STUD PULLERS



Small turning radius clears many obstructions that interfere with other types of pullers. Deeply serrated wedges grip tighter under pressure, hold stubborn studs firmly Can be used with hand or power tools. Complete with two wedges.

No. Description Wt. lbs.

1/2" square drive for studs
1/4" to 5/8"


4532 3/4" square drive for studs
5/8" to 1"

3.4

SHOP FROM THE COLORFUL P & C TOOL MERCHANDISERS

in your local stores. Wherever you see the eye-catching P&C Tool displays you'll find a dealer who knows quality. Buy from him. He will help you. And the P&C Tools he sells you are backed by a solid guarantee.

PED TORQUE WRENCHES



The newest thing in torque wrenches. No dials, no clicks, resets automatically Just set easy-to-read dial and puli. Release and resets automatically when the proper torque is reached. Precision made, sturdy, of special analysis alloy steel. All chrome finish

Foot Pound

Capac- Gradu-						
	quare Drive	ity a	tion Ft.	8.		Wt
	Size	lbs		Head	Length	lbs
6305	3/8"	5-75		Plain		1.34
6306	3/8"	5-75	1 F	latchet	141/16"	1.54
6307	1/2"	5-75	1	Plain	131/4"	1.34
6308	1/2"	5-75	1 F	latchet	14550"	1.54
6315	1/2"	10-150	2	Plain	171/4"	2.00
6316	1/2"	10-150	2 F	latchet	18%"	2.50
6317-	Į.					
	3/4"	500		Plain		8.8
6361-	F					
	1/4"	150		Plain		.85

Inch Pound

Capac- Gradu-Square ity ations. Drive In. In. Wi to. Size lbs. ibs. Head Length lbs. 6366 3/8" 100-750 5 Ratchet 141/10" 1.50 6371-F 3 4" 4800 Plain 8.8

ETE SPECIAL PURPOSE TOOLS

BRAKE ADJUSTING TOOLS



Biades forged at proper angle for easy quick adjustment of star nut on 2-shoe Bendix brakes found on most cars and trucks. Each blade 14" long.

No. Length Spoons Wt. lbs. 302 7" 156" .15 303 8½" \ 13\frac{13}{10} \text{ and } 1\frac{7}{10}" .18

GASKET SCRAPER



For removing shellacked gaskets, carbon, etc. Many uses.

No. 2336 Blade width 1½" Length 11½" Wt. .39 lbs.

LINING UP BARS

Forged from special alloy steel, heat treated for extra strength.

No.	Stock Size	Length	Wt. lb.
101	1/2"	14"	.65
102	5/8"	18"	1.33
103	3/4"	24"	2.55

ROLLING HEAD BARS



New type gear bar, with 90° rotting head. One of the handlest types of bars you can own, having a great many uses. Especially valuable for getting into close places, such as behind gears. Forged from alloy steel.

No. Stock Length Wt. 2126 1/2" Octagon 16" .86 lbs. 2130 5/8" Octagon 18" 1.62 lbs.

FORD V-8 CONNECTING ROD SOCKET



Thin nose %10" Hexagon socket, essential for Ford V-8 connecting rods, 1/4" square drive.

No. 2018 Opening 9/16" Length 11/2" Wt. .1 lbs.

CAD. AND LaSALLE CON. ROD SOCKET



Thin nose 6 point hex, 1/2" drive socket fits connecting rod nuts on Cadillacs and LaSalles.

No. 6522 Opening 7/16" Length 15/4" Wt. 13 lbs.

FORD V8-85 VALVE LIFTER

Extra length gives leverage to break loose toughest guides. Push guide down to remove keeper, then pry to force out guide.

No. 6539 Stock 3/4" Length 30" Wt. 3.5 lbs.

PISTON RING COMPRESSOR



Ratchet type, 3½" wide band expands from 2½'16" to 5". Two narrow outside bands take strain, prevent flaring, ring breakage. Dual ratcheting synchronizes both bands. Each ratchet tooth compresses diameter .003". Simple trigger locks, releases. L-Handle, fits ½" square drive, furnished with each compressor

No. 2316 Piston Ring Compressor Wt .85 lbs.

OBSTRUCTION WRENCHES 12 point Box



The wrench that really works around corners. Handy for removing, replacing many starter motors,

No.	Opening Sizes	Length	Wt. lbs.
1725	7/16"x1/2"	511/10"	.12
1730	9/16"x5/8"	621/32"	.20
1731	5/8"x3/4"	7%"	.33

CARBURETOR JET WRENCH



Fits nearly all types of Stromberg carburetors. Has cross pin and knurled grip for easy turning.

No. 4528 Length 2516" Wt. .06 lbs.



This handy tool is designed to pick up small objects even in hard-to-reach spots. It has four powerful "fingers" that reach out from flexible spring and securely grasp small items. Four sizes

No.	2340	12"	Wt	.09	lbs.
No.	2341	15"	Wt.	.12	ibs.
No.	2342	18~	Wt.	.15	lbs.
No.	2343	24"	WŁ	.19	lbs.


FFELER GAUGES

SHORT BLADES

1/2" wide, 3¼" long

		Wt.			Wt.
No.	Thick	lbs.	No.	Thick	lbs.
0015	.0015"	.001	014	.014"	.006
002	.002"	.001	015	.015"	.007
003	.003**	.002	016	.016"	.008
004	.004**	.002	017	.017"	.008
005	.005"	.003	018	018"	009
006	.006"	.003	019	019"	009
007	.007~	.004	020	.020"	010
800	.008"	.004	022	.022"	.011
009	.009*	.004	025	.025"	.012
010	,010"	.005	026	.026"	.013
011	.011"	005	030	030"	013
012	.012"	.005	032	.032"	.015
013	.013*	.006	035	.035"	.016
			040	.040"	.017

STANDARD FEELER GAUGE SET



Nine short blades in 000-C Holder. Thicknesses are 003", .004", .005", .006", .008", .010", .012", .015", and .018".

No. 000-A Standard Feeler Gauge Set Wt. .09 lbs.

No. 800-AA 25 Short Blades 8015 through 040 except 619 in 600-C holder. Weight .19 lbs.

LONG BLADES

1/2" wide, 12" long

				_	
		WŁ			Wt.
No.	Thick	lbs.	No.	Thick	lbs.
0015-1	.0015"	.002	017-L	.017~	.028
002-L	.002"	.004	018-L	.018"	.030
003-L	.003"	.006	019-L	019~	.031
004-L	004"	.008	020-L	.020"	.032
005-L	.005"	.009	021-6	021"	035
006-L	.006"	.012	022-L	.022"	.036
008-L	.008"	016	025-L	.025"	.040
010-L	.010"	.019	027-L	.027~	.043
011-L	.011"	.019	028-L	.028~	.046
012-L	.012"	.021	030-L	.030~	050
013-L	.013~	.023	032-L	032"	.054
014-L	.014"	.023	035-L	.035"	.057
015-L	.015"	.027	040-L	.040"	.070
016-L	.016"	.027			

FEELER GAUGE HOLDER

Holds all available sizes of 3¼" long feeler blades.

No. 000-C Length 3%" Wt. .05 lbs.

STEP-CUT FEELER GAUGES



"Go" and no-go" gauges, with two different thicknesses on each blade, 1/2" wide, 3/4" long.

No.	Thick	Wt. lbs
004/6	.004" & .006"	.002
005/7	.005" & 007"	.003
006/8	.006" & "600."	.003
007 9	.007" & .009"	.004
008/10	.008" & .010"	.004
009/11	.009" & .011"	.004
010/12	.010" & .012"	.006
011/13	011" & .013"	.007
012/14	012" & 014"	.066
013/15	.013" & .015"	.007
014/16	.014" & .016"	.007
015/17	.015" & 017"	.008
016/18	016" & 018"	.008
017/19	017" & 019"	.009
018/ 20	.018" & 020"	1775
019/23	.019" & .021"	.010
020/22	.020" & .022"	.010

STEP-CUT GAUGE SET

Four gauges, Nos. 004/6, 006/8, 008/10, and 010/12, in No. 000-C Holder,

No. 000-8 Step-Cut Gauge Set Wt. .06 lbs.

No. 000-88 8 Step-Cut Blades 004/6 through 011/13 in 000-C holder. Wt. 08 lbs.

IGNITION GAUGE SET



Ten blades, 3_{16} " wide, $1\frac{1}{6}$ " long, in holder. Thicknesses are .011", .012", .014", .018", .020", .022", .025", .022", .022", .032", and .035". Blades are not sold separately

No. 000-D Ignition Gauge Set Wt. .03 lbs.

BRAKE GAUGE SET



Nine blades, \$\frac{3}{18}" wide, 4" long, in holder. Thicknesses are .006", .008", .010", .012", .014", .016", .018", .020", and .025". Blades are not sold separately.

No. 000-E Brake Gauge Set Wt. .04 lbs.

SPARK PLUG GAUGE SET



Eight bent-wire gauges for checking spark plug gaps, complete in holder. Diameters are .022", .025", .027", .028", .030", .032", .035", and .040".

No. 000-K Spark Plug Gauge Set Wt. .06 lbs.


NO. 000M BENT GAUGE SET

Eleven 4" by 43/6" bent blades -.006", .008", 010", .011", .012", .013", .014", .015", .016", .019" and .020" -in holder and plastic pouch. Wt., .15 ib.



SCREW AND PIPE EXTRACTORS

	Small		U.S.S. Screw	Drill	Min Pipe	
	End	Length	n Stze	Size	Size	Wt
No.	In.	In.	In	In.	In.	lbs
9521	%	29/10	14. 110	1/4	_	.02
9522	11/64	2%	%	216		02
9523	13/64	21/9	746	33/64	1/8	.04
9524	19		12. 1/16	319	1/4	,06
9525	11/12	31/4	5∕6	3/6	36	.10
9525B	27/14	31/4	3/4	1362		.12
9526	1/2	436	₹/8	950	1/2	.23
9527	1962	41/8	1, 11/6	2142	1/2	.40
9528	23/32	5%	1%, 1%	23/20	34	.65
9529	31/44	51/2	11/2	11/36	1	1.12



Includes 5 extractors, Nos. 9521, 9522, 9523, 9524, and 9525.

No. 9500-A Screw and Pipe Extractor Set Wt. 28 lbs.

DES BODY AND VENDER FOOLS

Heads on Hammers perfectly balanced with handles. Faces precision ground, highly polished. Heads forged from high grade alloy hammer steel. Carefully heat treated for proper temper and hardness, then normalized to relieve internal stresses from forging and heat treating. Heads fastened with corrugated wedges. Select, straight grain, white hickory handles. Dolly blocks highly polished surfaces ground and finished to stand up under long, hard use.

PER HAMMERS

LONG PECKING HAMMER



Long handle reaches to center of turret tops, eliminates uncomfortable reaching under high crowned surfaces. Gives 4½" clearance on long picking end and 3" clearance to the round ball pein face.

No. 1429 Length of head 9" Wt. .88 lbs. Length of hammer 17"

No. 1429# Handle only 1735" long Wt. .3 lbs. 3/8"x11/16" eye

MAGNETIC TRIM HAMMER



For trim and upholstery work. Magnetized head curves in the arc of a natural swing.

No. 1419 Length of head 5½"
Wt. .44 lbs
Length of hammer 12%"
No. 1419H Handle only 13½" long
Wt. .18 lbs.
11/32"x11/16" eye

DINGING HAMMER



Has large head for bumping and dinging bad dents into shape for finishing. 11/4" and 11/4" diam. faces are slightly crowned.

No. 1421 Length of head 6½"
Wt. 1.25 lbs.
Length of hammer 12½"
No. 1421H Handle only 13" long
Wt. .22 lbs.

13/32"x13/16" eye Page 17

LONG BODY FINISHING HAMMER



For crowned fenders and other places that require head clearance. 1\%" diam. round face is slightly crowned, has 3\%" clearance. Other face is 11\%" diam. cross pein with 4" clearance. Use to finish and reshape troughs and lipped or obstructed surfaces.

No. 1426 Length of head 7\%"
Wt. 1.03 lbs.
Length of hammer 12\%"

No. 1426# Handle only 13" long Wt. 22 lbs. 13/32"x13/16" eye

FINISHING HAMMER



Use the 1" wedge cross pein to caulk fender heads, drip mouldings, corners, and on all reverse curves. Has 2½" clearance. The 1%" diam. face is crowned and has 2" clearance.

No. 1427 Length of head 41/2" Wt. .50 lbs. Length of hammer 12%"

No. 1427M Handle only 13½" long Wt. .18 lbs. 11/32"x11/16" eye

SHORT PECKING HAMMER



The 3" pointed end picks out small dents, low spots, forms ridges. Finishing face is 1½" diam.

No. 1428 Length of head 5%" Wt. 86 lbs.

Length of hammer 12%" No. 1428H Handle only 13" long

Wt. .22 lbs. 13/32"x13/16" eye

BRASS HAMMER



A fine soft faced hammer, it has perfect balance between handle length and weight. Many uses.

No. 1430 Brass Hammer Wt. 1.75 lbs.

FINISHING HAMMERS



Light, well balanced for smooth finishmg. 1½" diam. round face has slight crown. Shrinking face is 1½, square No. 1424 Length of head 4" Wt. .64 lbs.

Length of hammer 12%" No. 1424H Handle only 131/2 long Wt. .18 lbs. 11/32"x11/16" eye

Heavier than No. 1424 for finishing heavier gauge metal. Faces 11/4" diam. and 11/4" square.

No. 1425 Length of head 4¼" Wt. .90 lbs Length of hammer 121/2" No. 1425H Handle only 13" long Wt., 22 lbs. 13/32"x13/16"



RADIUS DOLLY



To ding flat surfaces. The bottom and one side are flat, form a right angle. Other faces provide many useful radii. Both ends are highly crowned. No. 1454 19/32"x2310"x41/2" Wt. 29 lbs

NEW BEAD DOLLY



Combines spoon and dolly for work on roof rails, behind door and body posts. Use sharp tapered wedge to drive out roof rails behind brackets, and under fender braces. Long thin lip works in behind reinforcements and on corners and beading. No. 1455 11/4"x229/22"x47/10" Wt. 2.4 lbs.

EGG-SHAPED DOLLY



This useful and popular shape has many different curves and angles.
No. 1452 1%"x2½"x3¾" Wt. 3.1 lbs.

SHRINKING DOLLY



Usual shape and low crown. Ideal for shrinking body metal and to raise beads and moulding. No. 1457 114"x314s"x3540" Wt. 2.2 lbs.

RAILROAD OR GENERAL **PURPOSE DOLLY**



One of the most versatile blocks ever made. Hand and working surfaces are far apart to give protection when working with hot lead. Top surface is used for bumping or roughing out, bottom to work panels and fender skirts. Two flanging and beading lips and several differently crowned working faces fit contours of all bodies, fenders and doors. Has eight moulding and bead working surfaces and 71/2 square inches on the largest face. No. 1453 2%"x234"x23142" Wt. 2.9 lbs

SEMI-ELLIPTICAL HEEL DOLLY



Has two flat working surfaces and two that are crowned. Can be used in corners and on wide radii; suitable for shrinking metal. Handy to use in close

No. 1458 1316"x2%"x314" Wt. 2.2 lbs.

P&C FILE AND HOLDER

DOUBLE-FACED FLEXIBLE STRAIGHT FILE



Curved teeth cut fast on all body, fender and sheet metal work. Shaped teeth eliminate chips and prevent loading. Identical teeth on both sides double its service and life. When used with No. 1509 Adjustable File Holder, it works in concave (hollow) surfaces, on convex (rounded) areas, or as a straight flat file.

No. 1501 Length 14" Width 1%" Wt. .7 lbs.

ADJUSTABLE FILE HOLDER



Made of aluminum for light weight with ample strength. One simple adjustment makes file flat, concave or convex. Bolt which attaches file at heel of holder should be loosened before flexing. No. 1509 Length 18" Wt. 1.86 lbs.

P&C Quality . . . Page 18





Tapered handle aligns bolt holes. Offset handle to clear adjoining bolts, protect operator's hands. Hot forged from special analysis alloy steel, scientifically heat treated for greatest strength and longest wear. Perfectly balanced and comply with all Government specifications on structural wrenches. Sandblasted satin finish clear lacquer coated to resist rust.

No.	Opening Size	Length	Wt. lb
924	3/4"	11"	.8
926	13/16"	12%"	.9
928	7/8"	121/4"	.9
932	1"	13"	1.3
934	11/10"	14"	1.5
936	1%"	14"	1.5
940	11/4"	16"	2.5
942	15/16"	16"	2.5
946	17/10"	18"	3.8
948	144"	18"	3.8
952	15/6"	20"	5.8

SPECIAL

FOUR-WAY LUG WRENCHES



Forged from alloy steel and induction welded for greatest strength and durability. Hex openings of %", %", 1316", and %" fit lug nuts of practically all cars and trucks. P&C Blue finish polished sockets. Two sizes to clear wide fenders.

No. 1175 4-Way Lug Wrench Length 18" Wt. 3 lbs.

1176 4-Way Lug Wrench Length 21½" Wt. 3.2 lbs.

TIRE PRODDING AWL



Tapered blade spreads rubber while blunt point removes imbedded particles without danger of damaging tube. Wooden handle shaped to fit palm comfortably. Lacquered finish.

No. 230 Length 71/4" Wt. .1 lbs.

Hinged tray swings up with lid. Re-

tools. Heavy padlock hasp; convenient handles on each end; handsome blue



Paddle shaped blade lifts lurger area of tire from rim. Thin blade gives best balance with light weight. Usually purchased in pairs; curved pattern used with straight. Hot forged alloy steel with dipped satin finish.

No. Length Wt. lbs. 207 Straight blade 18" 2



MIDGET TOOL BOX



Pocket size, to keep 4" drive sockets and attachments, and other smaller tools in order.

No. 4795 Dimensions: 1"x21/4"x63/4" Wt. .52 lbs.




Stores 9300-NR 34" drive set or equivalent, with ease. Sturdy, can be fasten-ed to truck or tractor. Has padlock hasp and folding handle.

No. 5695 Dimensions: 4" x 4" x 21" Wt. 8.2 lbs.

No. 5696 Dimensions: 4" x 91/4" x 231/4" Wt. 16 lbs.


EXTRA HEAVY DUTY TOOL BOX



Big enough and strong enough for complete P&C 4" or I" drive socket sets and attachments. Welded, riveted and strongly reinforced. Handles at ends make carrying easy.

No. 5894 Dimensions: 5"x81/4"x30" Wt. 21 lbs.

movable tray and drop front make it easy to reach tools. Trays and bottom compartment provide plenty of room, are partitioned for sockets or small



Wt. 20 lbs. 9"x111/2"x201/2" 11/4"x51/4"x19" 11/4"x51/4"x19" 21/4"x43/4"x20" 6"x11"x20"

DELUXE MASTER TOOL CHEST



Smooth, rounded corners, correct pro-

portions, deluxe design and construc-

tion make this tool chest the type of

equipment any mechanic can be proud

Tray in top swings up with lid, is partitioned to keep small tools arranged in order. Drawers pull out with

finger pressure. Deep compartment gives plenty of room for dozens of tools. One padlock secures everything. Attractive blue wrinkle finish. No. 9990 Dimensions 131/8"x111/2"x241/2" Wt. 37 lbs.

to own.

JUNIOR TOOL BOX



carried, makes convenient trouble shooter's kit. Holds %" drive sockets and attachments, and other essential tools.

No. 5295 Dimensions: 11/2"x51/4"x181/2" Wt. 2.4 lbs.

STANDARD TOOL BOX

HIP ROOF TOOL BOXES



Versatile, roomy, adapted to any mechanic's needs. Convenient tote tray lifts out. Cover has sturdy, full length hinges, two spring clasps, padlock hasp and folding handle.

No. 9970 Dimensions: 54/x6"x20" Wt. 6.7 lbs.

83/4"x7"x19" Wt. 9.3 lbs.



No. 9980 Dimensions: 61/2"x9"x221/4" Wt. 11 lbs.

UTILITY TOOL CHEST

Drop front and socket tray at top make it easy to find tools. Handles at each end make chest easy to carry. Padlock hasp on cover.

P&C TOOLS WILL LAST LONGER AND GIVE BETTER SERVICE THAN ANY OTHER TOOLS YOU CAN BUY

No. 5495 Dimensions: 13/4"x81/4"x191/2" Wt. 4.1 lbs.

cover.

Ample room for 1/4" drive standard sockets and attachments. Two socket compartments full length of box. Small compartment for extra sockets, cotter keys and other parts. Hinged padlock hasp and folding handle on

Page 19

PAD METRIC SIZE WRENCHES

Metric size socket wrenches and combination box and open end wrenches are for cars, machinery, and equipment made in France, Italy, Germany and most other European countries except England, which generally use Whitworth standards.


METRIC SIZE SOCKETS %" Square Drive



12-Point Openings

	Opening		
No.	Size, MM	Inches	Wt. Lbs.
3008M	8	1"	.04
3009M	9	1"	.04
3010M	10	1"	.04
3011M	11	1"	.04
3012M	12	1"	.05
3013M	13	\$#	.07
3014M	14	1"	.07
3015M	15	1"	.07
3016M	16	1"	.10
3017M	17	11/16"	.10
3018M	18	11/10"	.13
3019M	19	13/10"	.17

METRIC SIZE COMBINATION WRENCHES



No.	Size, MM	Inches	Wt. Lbs.
2710M	10	41/2"	.06
2711M	11	51/4"	.10
2712M	12	51/4"	.10
2713M	13	6"	.14
2714M	14	61/4"	.20
2715M	15	71/4"	.27
2716M	16	71/2"	.27
2717M	17	81/4"	.34
2718M	18	81/4"	.34
2719M	19	91/4"	.45
2720M	20	101/4"	.55
2722M	22	111/4"	.65

36" DRIVE SOCKETS

EXTRA DEEP



Extra Deep 6-Point Openings (for use on hex balts or nuts)

No.	Opening Size	Length	Wt. Lbs
3114H	7/16"	21/4"	.10
3116H	1/2"	21/8"	.10
3118H	9/16"	21/4"	.12



SPECIAL TOOLS

Facilities at P&C for manufacturing top quality tools are available for production of special tools to meet exacting requirements of industry. We have supplied special tools in substantial quantity to meet the specifications of Government procurement offices, farm equipment manufacturers, woodworking, and other industries.

We welcome an opportunity to submit a quotation for a tool need not covered by our regular tool line. Send blueprints, sketch, or sample of tool needed, quantity desired, and required delivery. P&C quality workmanship can be assured in design and production, with an end product tailor-made to meet a specific need.

NEW 6-POINT P&C SOCKETS



1/2" DRIVE SOCKETS

6-Point Openings (for use on hex bolts or nuts)

No.	Opening Size	Length	Wt. Lbs
6016H	1/2"	1%"	.10
6018H	9/16"	1%"	.10
6020H	5/8"	136"	.13
6022H	11/16"	1%"	.13
6024H	3/4"	13/6"	.15

MORE MASTER CRAFTSMEN

ate using P & C Tools today than ever before. Electricians, plumbers, mechanics and hobbyists recommend P & C Tools.

OUR SLOGAN . . .

"P & C . . . the best tools money can buy" is a slogan that means a great deal to the skilled craftsmen who make P & C Tools. P & C Tools are carefully made according to the most rigid specifications. Only the finest special-analysis alloy steels are used. All P & C Tools are inspected before leaving our factories and they are fully guaranteed from defects in materials and workmanship.

If any P & C Tool ever proves detective, from causes other than normal wear or abuse, your P & C dealer will replace it or have it repaired at no cost to you. You'll be glad you bought P & C.

P & C
. . . THE BEST TOOLS
MONEY CAN BUY

You'll be a Tool Expert...

Read these important facts about how tools are made

Learn how P & C maintains quality in all P & C Tools



GLOSSARY of TERMS

CHAMFERED

The edges of P & C sockets and box wrenches are tapered to permit easier locating of the socket on the nut or bolt head.

CHROME PLATED

All alloy steels will oxidize or rust when exposed to air and moisture. To reduce this deteriorating process, all P & C tools are chrome plated or lacquered. Tools that are adaptable to the plating method are processed through a number of steps concluding with a coating of nickel and a coating of chrome. Punches and chisels are lacquer coated.

DROP FORGED

Formed by compressing hot metal between a pair of dies, the upper half of which is lifted by mechanical means, then dropped, forging the metal into the die cavities. Contrasted with "open" forming by hammer blows. Drop forgings are more accurate in dimension and have more strength.

GOVERNMENT SPECS

The U. S. Government buys huge quantities of hand tools for the armed services and civilian agencies. To maintain levels of product quality, specifications have been developed for dimensions and hardness. All P & C tools exceed by a comfortable margin these specifications.

GROUND

Accurately finished for the use intended, such as correctly dimensioned bits on screwdrivers to fit slotted screws. P & C screwdrivers are checked to meet close tolerance requirements.

HAND HONED SIDE CUTTERS

P & C side cutting plier blades are individually honed by hand to close tolerance—yet tough enough to cut through a nail without damaging the cutting edges. You'll find quality in P & C Tools that you don't find in others.

HEAT TREATED

Subjected to heat until it reaches a predetermined temperature, then cooled or "quenched" with water, oil or air to bring about the desired hardness and toughness. Teeth on P&C pliers and wrenches are heat treated to retain sharpness, maintain a positive sure grip.

HOT BROACHED

The openings of P & C sockets (that fit a nut or bolt) are "cut" or formed while the metal is heated to a high temperature to obtain benefits mentioned under "Hot Forged" below.

HOT FORGED

Formed at the proper temperature so that the steel molecules flow readily in the die cavities for maximum strength and durability. Every P & C Tool has a money back guarantee of quality. P & C Tools are stronger, tougher.

INDUCTION HARDENED

A method of tempering electrically whereby only a selected area is heat treated to the required hardness, leaving the surrounding area with tough qualities. P&C cutting edges are induction hardened against chipping and dulling. That is why P & C Tools outlast other tools.

INDUCTION WELDED

Welded together by a very high temperature induced electrically so that the two pieces of metal form a union that is stronger than either part.

OIL TEMPERED

First the tool is heated, then quenched in (dropped into) oil which is maintained at a specific temperature. This results in uniform "tempering."

SATIN FINISH

A tool finished by "sandblasting" with grit thrown from a revolving drum, to make a smooth but pebbly finish for a firm grip, yet easily kept clean.

SCREWDRIVER BIT

The portion of a screwdriver that fits the screw. There are two patterns of bits that fit a common cross slot screw. Keystone—where the blade is wider than the shank and is shaped like the key stone in an arch. Cabinet—blade is the same width as the shank and has straight sides. P & C screwdrivers are the best you can buy.

TORQUE TESTED

Checked on a torque measuring machine to be sure that the tool has sufficient twisting strength without bending or breaking. Commonly applied to sockets and wrenches. All P & C Tools are carefully inspected and tested before leaving our factories. They are rugged tools.

U. L. APPROVED

Approved by Underwriter Laboratories as meeting their rigid requirements for safety. P & C plastic screwdriver handles are regularly checked by U. L. inspectors to be sure that they continue to qualify as being fire resistant.



